

# WPL9010 Weigh Price Labeller

Manual weigh price labelling.



- Automatic stability sensing
- Overload protection
- Easy label editing
- Choice of operational modes



Marel's **WPL9010 Manual Weigh Price Labeller** is ideal for low volume labelling of individual packs, product development or products that are unsuited to automatic labelling.

Short production runs can be handled with ease, thanks to quick label changeover. The **WPL9010** uses the same operator friendly HMI as automatic models and requires no additional training for existing WPL9000 series users.

The **WPL9010** features various operational modes for catchweight and average weight.

In the inclusive/exclusive mode, maximum and minimum weight limits are set to give the user the choice of either labelling only packs that fall within these limits or labelling only packs that fall outside the limits.

In the combined catchweight/average weight mode, packs falling within the preset limit can be labelled as average weight with those outside the limits being labelled as catchweight.

The machine is available in three platform sizes and weighing ranges up to 30kg in increments as small as 1g.

For further information please logon to: [www.marel.com](http://www.marel.com)

## Key Features and Benefits

- User friendly on-screen programming (WYSIWYG) for fast set-up
- Various operational modes for increased flexibility
- Easy to use label design programme (Comformat editor)
- Automatic zeroing when the weigh platform is empty gives increased accuracy
- Automatic stability sensing for accurate weighing
- Ethernet networking capability and compatibility with Innova
- Also available without a printer for use as a Checkweigher
- Throughput speeds up to 20/min (operator dependant)
- Robust stainless steel construction
- Overload protection to help prevent accidental damage

## Technical Information

### Label sizes:

Minimum: 40 x 40 mm

Maximum: 100 x 150 mm

Maximum reel ø: 200 mm

Reel core size: 38 / 76 mm standard

### Standard Weighing Configurations:

20g to 1500g x 1g & 1500g to 4500g x 2g

(Marel PL2020: 250 x 300mm platform)

40g to 6000g x 2g

(Marel PL2020: 250 x 300mm platform)

100g to 15kg x 5g & 15kg to 30kg x 10g

(Marel PL3020: 290 x 390mm platform)

200g to 30kg x 10g

(Marel PL3020: 290 x 390mm platform)

200g to 30kg x 10g

(Marel PL4020: 400 x 550mm platform)

Accuracy Class III or IV

- Table top mounted as standard, mounting frames available on request
- IP54 rated (IP65 printer protection available for washdown)
- EMC environment classification E2

**Power requirement:** 110/230 VAC – 50/60Hz, 1 phase

NAWI European approval to Council Directive 2009/23/EC

