



GO

Celerway GO is the only portable, battery-powered mobile router to deliver Gigabit class connectivity with VPN encryption virtually anywhere, while being small enough to fit in your hand or stow in a laptop case.

Thanks to its innovative use of 2 simultaneous cellular WAN connections, GO gives teams working remotely—whether at stationary remote locations or on the go—seamless, secure access to company resources and IT infrastructure as if they'd never left the office.

Maximum load balancing capacity	950 Mbps
Phantom VPN encryption	180 Mbps
IPSec VPN encryption	60 Mbps
Maximum number of simultaneous WANs	5
Dimensions w x h x d	79 mm x 141 mm x 30 mm
Weight	0.33 kg
Operating temperature	5 °C to 35 °C
Humidity	5% to 85%
Power supply	USB-C 5V, 3A
Integrated cellular	1 x CAT12 or 2 x CAT12 depending on model
SIM card slot	2 x Micro
Ethernet (WAN and/or LAN)	2 x 10/100/1000 Mbps RJ-45
Wi-Fi (WAN and/or LAN)	2.4GHz + 5GHz simultaneous dual-band
USB	2 x USB-C (self-charging, other device charging)
Mini-PCIe	-
M.2	1 x or 2 x depending on model
Antenna connectors cellular	2 x SMA female
Antenna connectors WiFi	-
Antenna connectors GPS	-
Battery power rating	10000mAh
Operating time	7 hours

GO Double modem

3YP-CWY-M5.1-E2L2W2B

7090049150388

Theoretical Upload Rate 150 Mbps
+
150 Mbps

Theoretical Download Rate 600 Mbps
+
600 Mbps

LTE-FDD B1/B2/B3/B4/B5/B7/B8/B9/
B12/B13/B14/B17/B18/B19/
B20/B21/B25/B26/B28/B29/B30/B32/B66
+
B1/B2/B3/B4/B5/B7/B8/B9/
B12/B13/B14/B17/B18/B19/
B20/B21/B25/B26/B28/B29/B30/B32/B66

LTE-TDD B38/39/B40/B41
+
B38/39/B40/B41

WCDMA B1/B2/B3/B4/B5/B8/B19
+
B1/B2/B3/B4/B5/B8/B19

2xCA B1+3/5/18/19/20/26; B2+2/4/5/12/13/17/29/30/66;
B3+3/5/7/8/19/20/28;
B4+4(CA_4C only)/5/12/13/17/29/30;
B5+7/25/30/66; B7+7/20/28;
B12+25; B12+30; B13+66; B19+21; B20+B32;
B25+25; B25+26; B25+41; B29+30;
B38+38(CA_38C only); B40+B40; B41+B41; B66+B66;
+
B1+3/5/18/19/20/26; B2+2/4/5/12/13/17/29/30/66;
B3+3/5/7/8/19/20/28;
B4+4(CA_4C only)/5/12/13/17/29/30;
B5+7/25/30/66; B7+7/20/28;
B12+25; B12+30; B13+66; B19+21; B20+B32;
B25+25; B25+26; B25+41; B29+30;
B38+38(CA_38C only); B40+B40; B41+B41; B66+B66;

3xCA DL interband 3CA:
B1+3+5/7/8/19/20/28; B1+7+20;
B2+4+5; B2+4+13; B2+5+30; B2+12+30; B2+29+30;
B3+7+20; B3+7+28; B3+7+8;
B4+5+30; B4+12+30; B4+29+30; B5+66+2; B13+66+2;
B66+12+30; B66+29+30; B66+5+30; B2+B14+B66;

DL2 intraband plus interband 3CA:
B2+2+5; B2+2+13; B3+3+7; B3+7+7; B3+3+20;
B3+3+28; B3+3+1; B4+4+5; B4+4+13;
B7+7+28; B5+66+66; B13+66+66;
B66+66+2; B39+B39+B41; B39+B41+B41;
B14+B66+B66;

DL3 intraband 3CA:
B40+40+40; B41+41+41; B66+66+66;
+

DL interband 3CA:
B1+3+5/7/8/19/20/28; B1+7+20;
B2+4+5; B2+4+13; B2+5+30; B2+12+30; B2+29+30;
B3+7+20; B3+7+28; B3+7+8;
B4+5+30; B4+12+30; B4+29+30; B5+66+2; B13+66+2;
B66+12+30; B66+29+30; B66+5+30; B2+B14+B66;

DL2 intraband plus interband 3CA:
B2+2+5; B2+2+13; B3+3+7; B3+7+7; B3+3+20;
B3+3+28; B3+3+1; B4+4+5; B4+4+13;
B7+7+28; B5+66+66; B13+66+66;
B66+66+2; B39+B39+B41; B39+B41+B41;
B14+B66+B66;

DL3 intraband 3CA:
B40+40+40; B41+41+41; B66+66+66;

WiFi Theoretical Data Rate 300Mbps + 867Mbps

WiFi Protocol b/g/n + a/ac/b/g/n

WiFi Frequency 2.4GHz + 5GHz

Last modified 03-Jun-2021 02:49:38



At Celerway, we're on a mission
to keep business ahead of the
mobile curve.

© 2021 Celerway Communication AS
Lilleakerveien 2B, 0283 Oslo, Norway
+47 45 50 71 02 info@celerway.com

GO Single modem

3YP-CWY-M5.1-E2L1W2B

7090049150500

Theoretical Upload Rate	150 Mbps
Theoretical Download Rate	600 Mbps
LTE-FDD	B1/B2/B3/B4/B5/B7/B8/B9/ B12/B13/B14/B17/B18/B19/ B20/B21/B25/B26/B28/B29/B30/B32/B66
LTE-TDD	B38/39/B40/B41
WCDMA	B1/B2/B3/B4/B5/B8/B19
2xCA	B1+3/5/18/19/20/26; B2+2/4/5/12/13/17/29/30/66; B3+3/5/7/8/19/20/28; B4+4(CA_4C only)/5/12/13/17/29/30; B5+7/25/30/66; B7+7/20/28; B12+25; B12+30; B13+66; B19+21; B20+B32; B25+25; B25+26; B25+41; B29+30; B38+38(CA_38C only); B40+B40; B41+B41; B66+B66;
3xCA	DL interband 3CA: B1+3+5/7/8/19/20/28; B1+7+20; B2+4+5; B2+4+13; B2+5+30; B2+12+30; B2+29+30; B3+7+20; B3+7+28; B3+7+8; B4+5+30; B4+12+30; B4+29+30; B5+66+2; B13+66+2; B66+12+30; B66+29+30; B66+5+30; B2+B14+B66; DL2 intraband plus interband 3CA: B2+2+5; B2+2+13; B3+3+7; B3+7+7; B3+3+20; B3+3+28; B3+3+1; B4+4+5; B4+4+13; B7+7+28; B5+66+66; B13+66+66; B66+66+2; B39+B39+B41; B39+B41+B41; B14+B66+B66; DL3 intraband 3CA: B40+40+40; B41+41+41; B66+66+66;
WiFi Theoretical Data Rate	300Mbps + 867Mbps
WiFi Protocol	b/g/n + a/ac/b/g/n
WiFi Frequency	2.4GHz + 5GHz

Last modified 03-Jun-2021 02:49:49



Lilleakerveien 2B, 0283 Oslo, Norway
+47 45 50 71 02 info@celerway.com

At Celerway, we're on a mission
to keep business ahead of the
mobile curve.