



ALTOS

Altos is IP66 rated and enables up to 2 simultaneous WAN connections (1 cellular).

Choose Altos to keep remote devices connected in space-constrained areas and outdoors.

Maximum load balancing capacity	95 Mbps
Phantom VPN encryption	60 Mbps
IPSec VPN encryption	15 Mbps
Maximum number of simultaneous WANs	2
Dimensions w x h x d	45 mm x 180 mm x 45 mm
Weight	0.15 kg
Operating temperature	-20 °C to 60 °C
Humidity	5% to 95%
Power supply	Passive PoE 12–24V
Integrated cellular	1 x LTE
SIM card slot	Dual SIM 1 x full size (default) + 1 x micro
Ethernet (WAN and/or LAN)	1 x 10/100 Mbps RJ-45 (PoE)
Wi-Fi (WAN and/or LAN)	-
USB	-
Mini-PCIe	1
M.2	-
Antenna connectors cellular	N female
Antenna connectors WiFi	-
Antenna connectors GPS	-
Certification/rating	IP66

ALTOS

3YP-CWY-M9.1-E1L1

7090049150227

Theoretical Upload Rate 50 Mbps

Theoretical Download Rate 300 Mbps

LTE-FDD B1/B3/B5/B7/B8/B20/B28/B32

LTE-TDD B38/B40/B41

WCDMA B1/B3/B5/B8

2xCA B1+B1/B5/B8/B20/B28;
B3+B3/B5/B7/B8/B20/B28;
B7+B5/B7/B8/B20/B28;
B20+B32; B38+B38; B40+B40; B41+B41

Last modified 03-Jun-2021 02:51:02



At Celerway, we're on a mission
to keep business ahead of the
mobile curve.

© 2021 Celerway Communication AS
Lilleakerveien 2B, 0283 Oslo, Norway
+47 45 50 71 02 info@celerway.com