



CUMULUS

Cumulus enables up to 6 simultaneous WAN connections (1 cellular), providing connectivity with 4G backup for remote devices.

Choose Cumulus to connect ATMs, ticketing kiosks, and other POS devices.

Maximum load balancing capacity	95 Mbps
Phantom VPN encryption	60 Mbps
IPSec VPN encryption	15 Mbps
Maximum number of simultaneous WANs	6
Dimensions w x h x d	110 mm x 80 mm x 30 mm
Weight	0.50 kg
Operating temperature	-10 °C to 50 °C
Humidity	5% to 95%
Power supply	Barrel, 12V, 2A
Integrated cellular	1 x LTE
SIM card slot	2 x dual full size
Ethernet (WAN and/or LAN)	5 x 10/100 Mbps RJ-45
Wi-Fi (WAN and/or LAN)	2.4GHz
USB	1 x USB 2.0
Mini-PCIe	1
M.2	-
Antenna connectors cellular	2 x SMA female
Antenna connectors WiFi	2 x RP-SMA female
Antenna connectors GPS	-

CUMULUS DUAL SIM CAT6

3YP-CWY-M1.5-E5L1W1-CAT6

7090049150029

Theoretical Upload Rate 50 Mbps

Theoretical Download Rate 300 Mbps

LTE-FDD B1/B3/B5/B7/B8/B20/B28/B32

LTE-TDD B38/B40/B41

WCDMA B1/B3/B5/B8

2xCA B1+B1/B5/B8/B20/B28;
B3+B3/B5/B7/B8/B20/B28;
B7+B5/B7/B8/B20/B28;
B20+B32; B38+B38; B40+B40; B41+B41

WiFi Theoretical Data Rate 300Mbps

WiFi Protocol b/g/n

WiFi Frequency 2.4GHz

Last modified 03-Jun-2021 02:50:49



At Celerway, we're on a mission
to keep business ahead of the
mobile curve.

© 2021 Celerway Communication AS
Lilleakerveien 2B, 0283 Oslo, Norway
+47 45 50 71 02 info@celerway.com