



CIRRUS

With up to 7 simultaneous WAN connections (2 cellular), Cirrus provides the greatest resilience of our M2M products.

Choose Cirrus to connect remote devices such as point of sale (POS) kiosks when resilience is required.

Maximum load balancing capacity	95 Mbps
Phantom VPN encryption	60 Mbps
IPSec VPN encryption	15 Mbps
Maximum number of simultaneous WANs	7
Dimensions w x h x d	145 mm x 95 mm x 30 mm
Weight	0.40 kg
Operating temperature	-10 °C to 50 °C
Humidity	5% to 95%
Power supply	4-pin click, 9-18V, 2A, 40V with adapter cable
Integrated cellular	2 x LTE
SIM card slot	2 x full size
Ethernet (WAN and/or LAN)	5 x 10/100 Mbps RJ-45
Wi-Fi (WAN and/or LAN)	2.4GHz
USB	1 x USB 2.0
Mini-PCIe	2
M.2	-
Antenna connectors cellular	4 x SMA female
Antenna connectors WiFi	2 x RP-SMA female
Antenna connectors GPS	1 x SMA female

CIRRUS CAT4 Global

3YP-CWY-M2.1-E5L2W1-G

7090049150319

Theoretical Upload Rate 50 Mbps
+
50 Mbps

Theoretical Download Rate 150 Mbps
+
150 Mbps

LTE-FDD B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/ B19/B20/B25/B26/B28
+
B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/ B19/B20/B25/B26/B28

LTE-TDD B38/B39/B40/B41
+
B38/B39/B40/B41

WCDMA B1/B2/B4/B5/B6/B8/B19
+
B1/B2/B4/B5/B6/B8/B19

GSM/EDGE B2/B3/B5/B8
+
B2/B3/B5/B8

WiFi Theoretical Data Rate 300Mbps

WiFi Protocol b/g/n

WiFi Frequency 2.4GHz

Last modified 03-Jun-2021 02:50:36



At Celerway, we're on a mission
to keep business ahead of the
mobile curve.

© 2021 Celerway Communication AS
Lilleakerveien 2B, 0283 Oslo, Norway
+47 45 50 71 02 info@celerway.com