Green Pin® Sling Hook E EN 1677-2 GR8

Grade 8 eye sling hook EN 1677-2

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-2
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 * MPI b * DGUV *
- **Note:** from 8.2 t without flat part

CSO



for chain diameter		working load limit	length	diameter inside eye	width opening	thickness	width	diameter eye outside	width outside	length outside	width	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
5-6	3/16 - 7/32	1.12	84	23	26	15	20	43	72	114	10	6	0.28
7 - 8	1/4 - 5/16	2	103	26	30	20	24	51	87	139	12	8	0.56
10	3/8	3.2	128	35	33	24	29	65	106	172	15	10	1.09
13	1/2	5.4	152	41	37	32	39	77	133	209	18	12	1.98
16	5/8	8.2	190	52	44	40	44	94	165	255	21	16	3.55
18 - 20	3/4	12.8	237	60	61	49	62	115	208	327	28	21	7.1
22	7/8	15.5	280	72	75	54	65	132	242	375	30	23	9.9
26	1	21.6	259	70	73	70	75	144	235	371	37	37	13.3
32	1 1/4	32.8	299	66	87	78	89	150	281	430	42	42	21.6

* Excluding sizes 26 mm and 32 mm

Green Pin® Sling Hook CL EN 1677-2 GR8

Grade 8 clevis sling hook EN 1677-2

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-2
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI b DGUV

CSC



for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
5	3/16	0.8	76	7	26	15	20	28	72	108	6	0.29
6	7/32	1.12	75	7	26	15	20	28	72	108	8	0.29
7 - 8	1/4 - 5/16	2	95	9	30	20	24	32	87	136	9	0.58
10	3/8	3.2	113	12	33	24	29	42	106	164	13	1.1
13	1/2	5.4	138	15	37	32	39	54	133	208	16	2.12
16	5/8	8.2	161	19	44	40	44	68	165	240	20	3.67
18 - 20	3/4	12.8	198	23	61	49	62	82	208	305	24	7.32
22	7/8	15.5	236	25	75	54	65	97	242	350	28	10.63