

Universe	Professional
Type	Verticality
Category	Lanyards and energy absorbers
Subcategory	Fall arrest lanyards



JANE

Non-adjustable dynamic rope lanyard combines with an ABSORBICA energy absorber to create an I or Y energy-absorbing lanyard that helps hold the connector in position, with abrasion protection for the ends.

Short Description Non-adjustable dynamic rope lanyard

Selling Points

- Can be combined with an ABSORBICA energy absorber to set up an energy-absorbing I or Y lanyard with a maximum length of two meters
- Sewn ends protected by plastic sheath to hold the connector in place and protect the ends from abrasion
- May be used with an MGO OPEN 60 connector with very large gate opening for connection to metal structures or to large-diameter cables and bars
- Available in several lengths: 0.6, 1 and 1.5 m

Specification

- Certification(s): CE EN 354, EAC

Specifications by reference

Reference(s)	L50 60	L50 100	L50 150
			
Length	60 cm	100 cm	150 cm
Weight	110 g	130 g	185 g
Made in	DE	DE	DE
Guarantee	3 years	3 years	3 years
Packing	1	1	1
Case quantity	40	30	30
EAN	3342540028258	3342540025769	3342540029163

Related product(s) MGO OPEN 60
RING OPEN
ABSORBICA
MICRO SWIVEL