

Premium Acrylic Paint 8200



PHYSICAL PROPERTIES :

Premium paint is a high grade Acrylic paint formulated for maximum coverage at an economical cost over concrete or stucco. It is formulated to cover in one application at approximately 0.5 gal per square. This formula is made to cover and adhere to a slightly chalky surface.

SPECIFICATIONS IN PACKAGES

Non-Volatile Liquid Elastomer	26%
% Pigments	37%
% Solvents	37%
Container Stability	12 months

TYPICAL PROPERTIES OF CURED COATINGS

Flash Point	None
Dry Time at 77°F	
To Touch	3 hours
Throughout, Days	1 day
Film Thickness of 1 gal/100 square feet	8 mils
Color Stability	Excellent
Temperature Range	
Application Degree F	50 - 120°F
Service Degree F.	-10 - 180°F
Resistance to:	
Oil	Good
Sunlight	Excellent
Chemicals	Excellent
Ozone	Excellent
Permeability, Water Vapor ASTM E-96	5 U.S. Perms
Weathering Effect	Excellent
Adhesion: Urethane Foam	Good
Concrete, stucco	Excellent
Wood	Excellent
Cold Temperature Flexibility	Good
Abrasion Resistance	Good
Resistance, Foot Traffic	Fair

8200