



ROOFERSworld

HARNES MOUNT™

WARNING

This re-useable temporary roof anchor is part of a temporary fall arrest system. The users must read and understand other manufacturer's instructions for each component or part of the complete system. Alterations or misuse of this product or failure to follow instructions, may result in serious injury or death.

INSTRUCTIONS

This re-useable temporary roof anchor is designed for personal fall protection for one person only.

It is NOT TO BE USED for attaching mechanical equipment or staging. Meets all 5,000 lbs. load requirements of OSHA 1926.500 and OSHA 1910.66, as well as ANSI Z359.1

- 1) Position the roof anchor directly over the truss or rafter at the ridge apex (truss must be capable of supporting 5,000 lbs.)
- 2) Fasten to roof using 6 holes on both sides of the bracket using 3" galvanised screws. Drive outer screws into truss or rafter at an inward angle to ensure contact.
- 3) Inspect the ridge anchor assembly before use and do not use if there are visible defects.



WORKER SAFETY FIRST

- Safe and secure temporary roof ridge anchor for fall-arrest harness
- Meets OSHA guidelines for all safety attachments in steep slope environments
- Tested to 5000 lbs.
- Powder coated with durable anti-corrosion paint, zinc plated tie-off mechanism, made with high-grade carbon steel



QUESTIONS?

LUCIE QUIGLEY
LUCIE@ROOFERSWORLD.COM
C. 902.891.1973

FOLLOW US ON SOCIAL MEDIA



ROOFERSWORLD.COM