

Model	Standard	Category
L-7295	EN ISO 20345:2011	S1P SRC

**Images**



- Upper:** High Quality Cow Suede Leather
- Lining:** Breathable Sandwich Air Mesh
- Insock:** Comfortable Mesh Coated EVA
- Outsole:** PU/PU dual density
- Tested :** By UK Intertek Lab (Approved body:0362)
- Toe:** Steel Toecap to Resist 200 Joules Impact
- Penetration:** Steel Plate to Resist 1100 Newtons Puncture
- Size:** Euro 37-47#, UK 3-13# , US 4-14#

SRC

SRC (SRA+SRB)

	PU - PU	PU - PU
SRA CERAMIQUE EAU ET	PU P > 0.32 SRA > 0.28	0.52 0.48
SRB POLY GLYCERINE	PU P > 0.18 SRA > 0.13	0.23 0.18

EN ISO 20345:2011



**Weight & Packages**

1. Weight: 1.1-1.2 KGS/Pair
2. Each pair is packed in one color box, box size: 32\*21\*12CM
3. 10 pairs are packed in one carton, carton size: 62\*43\*33CM

**User Instructions & Storage**

1. **RECOMMENDED TO USE:** Basic workplaces, Construction, Logistics, Mechanics, Glasses installation, Workshop, Farming, Garden, Car repair shop etc.
2. **LIMITATION TO USE:** It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
3. **FITTING & SIZE:** All footwear are marked with standard size on tongue label. Some with different size comparison, such as EU size, US size, UK size etc. Please wear footwear by a suitable size. Footwear which are too loose or too tight may not provide optimum level of protection.
4. **STORAGE:** Keep in its original packaging, under ordinary temperature and non-humidity conditions and in clean, covered and ventilated premises.
5. **CLEANING:** Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.

**Outsole Material:**  
The outsole is made of PU/PU material in dual density. The midsole is 45 degree hardness PU, which is soft and shock absorption. The outsole is 60-65 degree hardness PU, which is tough and abrasion resistant. The outsole can pass SRC slip-resistant test.

**Insock Material:**  
  
J-001 insock design, the ventilation fabric can absorb 90% sweat and dry feet efficiently. U-design support heel can disperse human weight pressure, and reduce friction between feet and shoes. EVA material is soft and flexible, to increase comfortability during walk.

**Toecap Protection:**  
  
Stainless steel toe cap can reach 200 joules. It is more strong than iron toe cap.

**Penetration Protection:**  
  
Steel midsole plate, is zero-penetration resistant, which can resist 1100 newtons nail puncture. It is more strong and flexible than normal iron plate.