

Model	Standard	Category
L-7247	EN ISO 20345:2011	S1P SRC

Images



- Upper:** High quality smooth cow leather
- Lining:** Anti-abrasion pigskin leather
- Insock:** Comfortable mesh coated EVA
- Outsole:** PU/PU injection, dual density
- Tested :** By UK Intertek lab (Approved body:0362)
- Toe:** Steel toe cap to resist 200 joules impact
- Penetration:** Steel plate to resist 1100 newtons puncture
- Size:** Euro 36-47#, UK 3-13#

SRC		
SRC (SRA+SRB)		
SRA CÉRAMIQUE EAU ET	PLAT ≥ 0.32 INCLINÉ ≥ 0.28	0.52 0.48
SRB PÉTROLE GLYCÉRINE	PLAT ≥ 0.18 INCLINÉ ≥ 0.13	0.23 0.18

Scale 81
PU - PU
EN ISO 20345:2011



Weight & Packages

- Weight: 1.2-1.3 KGS/Pair
- Each pair is packed in one color box, box size: 32*23*12CM
- 10 pairs are packed in one carton, carton size: 62*48*33CM

Usage & Stock method

- RECOMMENDED TO USE:** Basic workplaces, Construction, Logistics, Mechanics, Glasses installation, Workshop, Farming, Garden, Car repair shop etc.
- LIMITATION TO USE:** It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
- FITTING & SIZE:** All footwear are marked with standard size on tongue label. Some with different size comparison, such as EU size, US size, UK size etc. Please wear footwear by a suitable size. Footwear which are too loose or too tight may not provide optimum level of protection.
- STORAGE:** Keep in its original packaging, under ordinary temperature and non-humidity conditions and in clean, covered and ventilated premises.
- CLEANING:** Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.

Outsole material:

The outsole is made in PU/PU dual density. The midsole is 45 degree hardness PU, which is soft and shock absorption. The outsole is 60-65 degree hardness PU, which can pass SRC slip-resistant test.

Insock material:



J-002 insock design, the ventilation fabric can absorb 90% sweat and dry feet efficiently. U-design support heel can disperse human weight pressure, and reduce friction between feet and shoes. High density EVA material is soft and flexible, to increase comfortability during walk.

Toe protection:



Steel toe cap can reach 200 joules. It is light and anti-magnet, compared with steel toe cap.

Penetration protection:



Steel plate, to resist 1100 newtons nail puncture. It is more light, flexible and anti-magnet, compared with steel plate.