Anti-scratch UV / IR Shock

Safety Spectacle
Model: GUL CLEAR

STANDARD : IS 5983, ANSI Z87.1, EN 166, CE

INDUSTRY	IDEAL APPLICATIONS
Construction & projects	Material handling
Cement	Dusty area
Automotive	Assembly line
Power & utilities	Packaging
Metals & minings	Medical applications

SPECIAL FEATURES

LIGHT WEIGHT | 99.9% UV PROTECTION | HARD COATING | LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	Full wrap with side protection
Nose bridge	Nylon 6	Bridge is a part of the frame
Nose pad	TPR	Bridge is a part of the frame
Sleeve	Nylon 6	4 length position adjust
Temple	Nylon 6	Adjustable
Hinge / screw	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-1.2	F (45m/s)	K	26 g.

FEATURES
Brow guard temple with polycarbonate lens
Lens provides side protection
Hard coating on lens
Lens filters out 99.9% of harmful UV light
Lens provides perfect impact protection around the eyes
Length adjustable temple for all head sizes
Modern temple design & soft nylon temple tips contours to fit head shapes without stress
Credibly light, resilient & durable protective eyewear for all day wear
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

APPLICATION
Protects eyes exposed to low-level impacts
Best used for protection against flying small fragments

STORAGE
Can be stored in the dark for up to 2years
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING	PACKING
Clean it with the soft cloth	100 pieces per carton