

SPX FULL SYN UNIVERSAL MV ATF

MULTI-PURPOSE FULL SYNTHETIC AUTOMATIC TRANSMISSION FLUID THAT MEETS VARIOUS OEM SPECIFICATIONS

SPX Full Syn Universal MV ATF is formulated from premium quality synthetic base oils blended with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion and wear protection, and heat resistance. This complex fluid is compounded with a friction-modifying additives to provide smooth lock-up of clutches without chatter.

Advantages

- Excellent wear protection
- Quiet, smooth operation
- Superior thermal and oxidation stability compared to conventional ATF Fluids
- Protects against rust and corrosion
- Outstanding seal compatibility, will not degrade nylon components
- Dyed red to detect leaks
- Multi-functional fluid for reduced inventory

Applications

- Automatic transmissions from the makes of major OEMs such as GM, Ford, Chrysler, Toyota/Lexus, Nissan/Infinity, and Honda/Acura and others

Note: not recommended wherever CVT, DCT, Type F applications.

Specifications

SPX Full Syn Universal MV ATF is designed for use in most planetary geared automatic transmissions. Please consult the application chart for detailed suitability of use.

Note: not for sale in CA

TYPICAL PROPERTIES

Color, ASTM D1500	Red
Flash Point (COC), °C (°F)	204 (399)
Pour Point, °C (°F)	-50 (-58)
Viscosity	
cSt @ 40°C	32.0
cSt @ 100°C	6.3
Viscosity, Brookfield	
cP @ -40°C	12,100
Viscosity Index	153

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).

Web: www.pilotthomas.com

Email: info@spx-usa.com

Tel: 844.785.8326



Page: 1 of 1

Date: 03.31.21



Automotive

