

# SPX SELECT SYN BLEND SP/GF-6

## ENGINE OIL FOR PASSENGER CAR VEHICLES

SPX Select Syn Blend SP/GF-6 is an automotive engine oil formulated with premium API Group II & Group III base oils and premium additives. It provides good wear protection, sludge control, and protection against rust and corrosion. The formulation is compatible with current emission control systems and meets standard API and ILSAC specifications.

### Advantages

- Formulated to be compatible with emission control system catalysts
- Good resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge, varnish formation, rust, bearing corrosion, and wear

### Applications

- Gasoline direct-injection, conventional gasoline-fueled passenger cars, light trucks, and SUVs
- Four-stroke gasoline engines in other mobile or stationary equipment

### Specifications

SPX Select Syn Blend SP/GF-6 meets the following industry and OEM certifications:

- API SP (SAE 5W-20, 5W-30, 10W-30, 10W-40 & 20W-50)
- ILSAC GF-6A (SAE 5W-20, 5W-30, & 10W-30)
- Chrysler MS-6395 (SAE 5W-20, 5W-30, & 10W-30)
- Ford WSS-M2C960-A1, WSS-M2C945-B1 (SAE 5W-20)
- Ford WSS-M2C961-A1, WSS-M2C946-B1 (SAE 5W-30)
- GM 6094M (SAE 5W-20, 5W-30, & 10W-30)

## TYPICAL PROPERTIES

SAE Grade	5W-20	5W-30	10W-30	10W-40	20W-50
Specific Gravity @ 60°F	0.86	0.86	0.87	0.87	0.88
Density, lbs/gal @ 60°F	7.2	7.2	7.2	7.2	7.3
Flash Point (COC), °C (°F)	>200(>392)	>200(>392)	>220(>428)	>220(>428)	>220(>428)
Pour Point, °C (°F)	-45(-49)	-45(-49)	-40(-40)	-36(-33)	-30(-22)
Viscosity					
cSt @ 40°C	48.7	59.7	67.2	95.0	175.0
cSt @ 100°C	8.2	9.9	10.9	14.0	19.0
Viscosity Index	142	152	154	151	123
Cold Cranking Viscosity, cP @ (°C)	6000(-30)	5400(-30)	5000(-25)	6800(-25)	8000(-15)

Minor variations in typical properties data are to be expected in normal manufacturing.

### Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).

Web: [www.pilotthomas.com](http://www.pilotthomas.com)

Email: [info@spx-usa.com](mailto:info@spx-usa.com)

Tel: 844.785.8326



Page: 1 of 1

Date: 10.12.21



Automotive

