

SPX SELECT SYN BLEND HM SP/GF-6

ENGINE OIL FOR HIGH MILEAGE PASSENGER CAR VEHICLES

SPX Select Syn Blend HM SP/GF-6 is an automotive engine oil formulated with premium API Group II & Group III base oils and premium additives. It provides good wear protection, sludge control, and protection against rust and corrosion. The formulation is compatible with current emission control systems and meets standard API and ILSAC specifications. SPX Select Syn Blend HM SP/GF-6 is recommended for vehicles where excessive mileage is a concern with respect to engine age and onset wear.

Advantages

- Formulated to be compatible with emission control system catalysts
- Good resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge, varnish formation, rust, bearing corrosion, and wear
- Includes higher levels of detergency for vehicles with aging engines

Applications

- Gasoline direct-injection, conventional gasoline-fueled passenger cars, light trucks, and SUVs
- Four-stroke gasoline engines in other mobile or stationary equipment

Specifications

SPX Select Syn Blend SP/GF-6 meets the following industry and OEM certifications:

- API SP (SAE 5W-30)
- ILSAC GF-6A (SAE 5W-30)
- Chrysler MS-6395 (SAE 5W-30)
- Ford WSS-M2C961-A1, WSS-M2C946-B1 (SAE 5W-30)
- GM 6094M (SAE 5W-30)

TYPICAL PROPERTIES

SAE Grade	5W-30
Specific Gravity @ 60°F	0.86
Density, lbs/gal @ 60°F	7.2
Flash Point (COC), °C (°F)	>200(>392)
Pour Point, °C (°F)	-45(-49)
Viscosity	
cSt @ 40°C	59.7
cSt @ 100°C	9.9
Viscosity Index	152
Cold Cranking Viscosity, cP @ (°C)	5400(-30)

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).

Web: www.pilotthomas.com

Email: info@spx-usa.com

Tel: 844.785.8326



Page: 1 of 1

Date: 10.12.21



Automotive

