

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
 Date of issue: 11/19/2007 Revision date: 12/22/2021 Supersedes: 11/19/2007

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : SPX SELECT FULL SYN SP/GF-6  
 Synonyms : SPX SELECT FULL SYN 0W-16 SP/GF-6B  
 SPX SELECT FULL SYN 0W-20 SP/GF-6A  
 SPX SELECT FULL SYN 5W-20 SP/GF-6A  
 SPX SELECT FULL SYN 5W-30 SP/GF-6A  
 SPX SELECT FULL SYN 10W-30 SP/GF-6A

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : PASSENGER CAR ENGINE OIL

#### 1.3. Supplier

##### Manufacturer

Pilot Thomas Logistics  
 1051 Mustang Drive, Suite  
 600 Grapevine, TX 76051  
 T: 844-785-8326  
 www.pilotthomas.com



#### 1.4. Emergency telephone number

Emergency number : PERS: 1-800-633-8253  
 CUSTOMER #1898

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

|              |      |  |
|--------------|------|--|
| Eye Irrit. 2 | H319 | Causes serious eye irritation                |
| Asp. Tox. 1  | H304 | May be fatal if swallowed and enters airways |

Full text of hazard classes and H-statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H304 - May be fatal if swallowed and enters airways  
 H319 - Causes serious eye irritation

Precautionary statements (GHS-US) : P264 - Wash hands thoroughly after handling.  
 P280 - Wear protective gloves, eye protection.  
 P301+P310 - If swallowed: Immediately call a doctor  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes.  
 Remove contact lenses, if present and easy to do. Continue rinsing  
 P331 - Do NOT induce vomiting.

# SPX SELECT FULL SYN SP/GF-6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P337+P313 - If eye irritation persists: Get medical advice/attention.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name   | Product identifier   | %          | GHS-US classification  |
|--|----------------------|------------|--|
| Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%)                     | (CAS-No.) 64742-54-7 | <= 50      | Asp. Tox. 1, H304  |
| Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%)                      | (CAS-No.) 64742-55-8 | <= 50      | Asp. Tox. 1, H304  |
| Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts | (CAS-No.) 84605-29-8 | 0.25 - 2.7 | Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Aquatic Chronic 2, H411 |

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical attention.

First-aid measures after skin contact : Wash skin with mild soap and water.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Never give anything by mouth to an unconscious person. To prevent aspiration, keep head below knees. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into lungs. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

### 4.3. Immediate medical attention and special treatment, if necessary

All treatments should be based on observed signs and symptoms of distress in the patient.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry chemical, CO<sub>2</sub>, or water spray or regular foam.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Specific hazards arising from the chemical

Reactivity : No dangerous reactions known.

# SPX SELECT FULL SYN SP/GF-6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus. Fire-resistant protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Avoid all eye and skin contact and do not breathe vapor and mist. Wear suitable gloves. Nitrile gloves. VITON gloves. Use splash goggles when eye contact due to splashing is possible.

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Do not discharge into drains or the environment. May cause long lasting harmful effects to aquatic life.

### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Contain and/or absorb spill with inert material, then place in suitable container.

Methods for cleaning up : Large Spills: Dike far ahead of spill for later disposal. Use a non-combustible material like vermiculite, sand, or earth to soak up the product and place into a container for later disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.

### 6.4. Reference to other sections

Reference to other sections (8, 13).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Product can accumulate electrostatic charges that may cause fire by electrical discharges. Never use pressure to empty container. Over pressure may rupture containers, cause serious injury, cause or accelerate fire.

Precautions for safe handling : Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

Hygiene measures : Smoking, eating and drinking should be prohibited in areas of storage and use. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Take precautionary measures against static discharge. Store in a well-ventilated place. Keep container tightly closed.

Incompatible materials : Strong oxidizers. Strong acids.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7) |                                     |                      |
|---|-------------------------------------|----------------------|
| ACGIH   | ACGIH TWA (mg/m <sup>3</sup> )      | 5 mg/m <sup>3</sup>  |
| ACGIH   | ACGIH STEL (mg/m <sup>3</sup> )     | 10 mg/m <sup>3</sup> |
| OSHA  | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 5 mg/m <sup>3</sup>  |

# SPX SELECT FULL SYN SP/GF-6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8) |                                 |                      |
|--|---------------------------------|----------------------|
| ACGIH  | ACGIH TWA (mg/m <sup>3</sup> )  | 5 mg/m <sup>3</sup>  |
| ACGIH  | ACGIH STEL (mg/m <sup>3</sup> ) | 10 mg/m <sup>3</sup> |

| Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8) |  |  |
|---|--|--|
| Not applicable  |  |  |

| Monitoring methods       |   |
|--------------------------|---|
| Monitoring methods (oil) | NIOSH Manual of Analytical Methods, Mixed Cellulose Ester Filter (MCEF) 0.8 microns |

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Avoid splashing. Avoid creating mist or spray. Either local exhaust or general room ventilation is usually required.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. VITON gloves. nitrile rubber gloves

#### Eye protection:

Use splash goggles when eye contact due to splashing is possible

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Use an approved respirator equipped with oil/mist cartridges or P100.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |                       |
|---|-----------------------|
| Physical state                              | : Liquid              |
| Appearance                                  | : Amber liquid.       |
| Color                                       | : amber               |
| Odor  | : petroleum-like odor |
| Odor threshold                              | : No data available   |
| pH  | : Not applicable      |
| Melting point                               | : No data available   |
| Freezing point                              | : No data available   |
| Boiling point                               | : > 315 °C            |
| Flash point                                 | : 215 °C              |
| Relative evaporation rate (butyl acetate=1) | : No data available   |

# SPX SELECT FULL SYN SP/GF-6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                 |  |
|---------------------------------|--|
| Flammability (solid, gas)       | : No data available                                |
| Vapor pressure                  | : < 0.01 mm Hg @ 37.8 C (100 F)                    |
| Relative vapor density at 20 °C | : > 1  |
| Relative density                | : 0.89 @ 15.6 C (60.1 F)                           |
| Solubility                      | : Soluble in organic solvents. insoluble in water. |
| Log Pow                         | : No data available                                |
| Auto-ignition temperature       | : No data available                                |
| Decomposition temperature       | : No data available                                |
| Viscosity, kinematic            | : No data available                                |
| Viscosity, dynamic              | : No data available                                |
| Explosive limits                | : No data available                                |
| Explosive properties            | : No data available                                |
| Oxidizing properties            | : No data available                                |

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

| Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7) |                |
|---|----------------|
| LD50 oral rat   | > 5000 mg/kg   |
| LD50 dermal rabbit  | > 2000 mg/kg   |
| LC50 inhalation rat (mg/l)  | > 5.53 mg/l/4h |

# SPX SELECT FULL SYN SP/GF-6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Distillates (petroleum), hydrotreated light paraffinic (DMSO &lt;3%) (64742-55-8)</b> |                          |
|--|--------------------------|
| LD50 oral rat  | > 5000 mg/kg body weight |
| LD50 dermal rabbit   | > 2000 mg/kg body weight |
| LC50 inhalation rat (mg/l)   | > 10.5 mg/l/4h           |

| <b>Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)</b> |                        |
|--|------------------------|
| LD50 oral rat  | 3100 mg/kg             |
| LD50 dermal rat  | > 2002 mg/kg           |
| LC50 inhalation rat (mg/l)   | > 2.3 mg/l/4h          |
| ATE US (oral)  | 3100 mg/kg body weight |

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

| <b>SPX FULL SYNTHETIC ENGINE OIL</b>     |                                     |
|--|-------------------------------------|
| IARC group                               | Not listed in carcinogenicity class |
| National Toxicology Program (NTP) Status | Not listed in carcinogenicity class |

: Not classified  
Reproductive toxicity  
Specific target organ toxicity – single exposure : Not classified  
Specific target organ toxicity – repeated exposure : Not classified  
Aspiration hazard : May be fatal if swallowed and enters airways.  
Viscosity, kinematic : No data available  
Likely routes of exposure : Dermal.  
Symptoms/effects after eye contact : Causes serious eye irritation.  
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : No ecotoxicological data about this product are known.

| <b>Distillates (petroleum), hydrotreated heavy paraffinic (DMSO &lt; 3%) (64742-54-7)</b> |              |
|---|--------------|
| EC50 Daphnia 1  | > 10000 mg/l |

| <b>Distillates (petroleum), hydrotreated light paraffinic (DMSO &lt;3%) (64742-55-8)</b> |                  |
|--|------------------|
| LC50 fish 1  | > 100 mg/l LL50. |

| <b>Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)</b> |          |
|--|----------|
| LC50 fish 1  | 4.5 mg/l |
| EC50 Daphnia 1   | 23 mg/l  |
| ErC50 (algae)  | 21 mg/l  |
| NOEC (acute)   | 1.8 mg/l |
| NOEC chronic crustacea   | 0.8 mg/l |

# SPX SELECT FULL SYN SP/GF-6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.2. Persistence and degradability

| SPX FULL SYNTHETIC ENGINE OIL   |   |
|---|---|
| Persistence and degradability   | This product is not expected to be biodegradable. |
| Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)                      |   |
| Persistence and degradability   | Not readily biodegradable.                        |
| Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8) |   |
| Biodegradation  | 1.5 % 28 days                                     |

### 12.3. Bioaccumulative potential

| Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8) |      |
|---|------|
| Log Kow   | 0.56 |

### 12.4. Mobility in soil

| SPX FULL SYNTHETIC ENGINE OIL |                                      |
|-------------------------------|--------------------------------------|
| Ecology - soil                | No additional information available. |

### 12.5. Other adverse effects

|                           |  |
|---------------------------|--|
| Effect on the ozone layer | : None known                           |
| Effect on global warming  | None known                             |
| Other information         | : No additional information available. |

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

|                                |   |
|--------------------------------|---|
| Waste disposal recommendations | : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. |
|--------------------------------|---|

## SECTION 14: Transport information

### Department of Transportation (DOT)

Not regulated.

### Transportation of Dangerous Goods

Not regulated.

### Transport by sea

Not regulated.

### Air transport

Not regulated.

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

| Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7) |  |
|---|--|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory       |  |

# SPX SELECT FULL SYN SP/GF-6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. International regulations

### CANADA

### Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

### Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on the Canadian DSL (Domestic Substances List)

### Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

### Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### National regulations

### Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on Taiwan National Chemical Inventory

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

### Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Not listed on the Inventory of Existing Chemical Substances of China (IECSC).

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on Taiwan National Chemical Inventory

Listed on the AICS (Australian Inventory of Chemical Substances)

## 15.3. US State regulations

No additional information.

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 07/09/2018



# SPX SELECT FULL SYN SP/GF-6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources : European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.  
European Chemicals Agency (ECHA) Registered Substances list. Accessed at <http://echa.europa.eu/>.  
Component Supplier SDSs.  
Manufacturer Information.

Full text of H-phrases:

|                   |  |
|-------------------|--|
| Aquatic Chronic 2 | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Asp. Tox. 1       | Aspiration hazard Category 1                                     |
| Eye Dam. 1        | Serious eye damage/eye irritation Category 1                     |
| Eye Irrit. 2      | Serious eye damage/eye irritation Category 2                     |
| Skin Irrit. 2     | Skin corrosion/irritation Category 2                             |
| H304              | May be fatal if swallowed and enters airways                     |
| H315              | Causes skin irritation   |
| H318              | Causes serious eye damage  |
| H319              | Causes serious eye irritation                                    |
| H411              | Toxic to aquatic life with long lasting effects                  |


Abbreviations and acronyms:

|  |
|--|
| ACGIH (American Conference of Government Industrial Hygienists)                |
| ATE: Acute Toxicity Estimate   |
| CAS (Chemical Abstracts Service) number  |
| GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). |
| IARC: International Agency for Research on Cancer                              |
| LD50: Lethal Dose for 50% of the test population                               |
| STEL: Short Term Exposure Limits   |
| TWA: Time Weighted Average   |

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Indication of changes:

| Section | Changed item                 | Change   | Comments                                      |
|---------|------------------------------|----------|---|
| 2.1     | Show classification (GHS US) | Added    |   |
| 2.2     |                              | Modified | Modified to be consistent with classification |

SDS US (GHS HazCom 2012)

# SPX SELECT FULL SYN SP/GF-6

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

SDS prepared by:

The Redstone Group, LLC

6077 Frantz Rd. Suite 206

Dublin, OH USA 43017

T 614-923-7472

[www.redstonegrp.com](http://www.redstonegrp.com).

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*