

TERRACLEAR

Common Compatible Compact Track Loader (CTL) Models

Brand	Model	Hydraulics	Extras	Operating Capacity
 JOHN DEERE	325G or greater	1 on/off	Closed cab	50% tipping load rating >2800lbs
 NEW HOLLAND AGRICULTURE	L328 or greater	1 on/off	Closed cab	50% tipping load rating >2800lbs
 CASE	TR310B or greater	1 on/off	Closed cab	50% tipping load rating >2800lbs
 CAT [®]	259D3 or greater	1 on/off	Closed cab	50% tipping load rating >2800lbs



TerraClear Bucket Dimensions

- Depth: 45 inches
- Height: 26 inches
- Width: 78 inches
- Volume: 7 cubic yards
- Distance between tines: 3 inches

Other Brands and/or Models: Kubota, JCB, etc. may be compatible. Please contact TerraClear

Operating capacity: Equivalent to 100% or full tipping load of 5600 lbs. Lighter compact track loaders with appropriate added weights may be compatible.

Mounting: Standard compact track loader backing plate

Hydraulics: Quick couplers may vary, so check compatibility with TerraClear. Minimum 18gpm flow/2900 psi.

Compact Track Loader Hydraulic Requirements

Flow

18 GPM minimum

Pressure

2900 psi minimum

Connections

The ones listed below are the default TC supplies and correspond with the most common style found on skid steers. TC can supply adapters to fit customer's needs.

Pressure



Non-spill, Flush face Quick Coupling, 1/2" Coupler

For example: Parker FEM-501-12F0-NL

Return



Non-spill, Flush face Quick Coupling, 1/2" Nipple

For example: Parker FEM-502-120F0