



SMOOTH LUBE

GENERAL DESCRIPTION

Smooth Lube is a water soluble lubricant used on chains, bearings and conveyors. It is uniquely formulated for use in water up to 10 grains (171 ppm) hardness, and will provide excellent cleaning, desired foam level and lubricity at recommended dilutions. Smooth Lube has been dynamically tested for extreme pressure lubricating properties utilizing the Falex EP Tester as well as practical field tests.

PHYSICAL PROPERTIES

APPEARANCE: clear, lemon coloured liquid

ODOR: negligible

DENSITY: 1.02 kg/L

DIRECTIONS FOR USE

Smooth Lube is recommended for use with soft or hard water (0-10 grains or 0-171 ppm).

The most economical dilution rate will be determined by your Food Safety Alliance representative. Dilution ratio does vary with conveyor loads, type of conveyor and water hardness. Typical dilution range is 1:100 to 1:200.

Do not use a dilution that results in a cloudy or milky solution as it tends to block lines and leave a residue on the conveyors. To correct this problem check your water softener and/or decrease dilution until solution is cleared.

CAUTION

This product contains Isopropanol (CAS No. 67-63-0).

Store only in the original vented containers. To ensure proper venting, keep drums upright and do not stack. Keep drums closed when not in use. Avoid damage to containers.

SAFETY

When handling concentrated chemicals, follow the guidelines listed in the Safety Data Sheets (SDS). PPE must be worn at all times. Avoid contact with skin and eyes. Wash thoroughly after handling. In case of contact, immediately flush skin or eyes with plenty of water. For eye contact, flush eyes thoroughly with water and seek medical attention immediately.