

SLX300 AUTOMATIC SLIDING DOOR



AUTOMATIC OPENING OF DOORS

The automatic, contact-free opening of doors makes our day-to-day lives easier and more convenient. Highly reliable Gilgen drive units provide trouble-free access from one room to another. The smooth automatic closing of doors induces a sense of well-being and security. This simple door operator fulfils, in a cost effective way, the structural needs of design and function.

Drive-system Components

- 1 Compact drive unit with electronically-controlled door operation, low maintenance with high performance
- 2 Running profile with replaceable track system - long life - low noise
- 3 Covering simple to secure in hinged-up position, lock in clips to end caps and bungee straps for optimum safety
- 4 Running carriage with three-dimensional compensation for structural tolerances and adjustable door suspension, height adjustment to + / -10mm, lateral adjustment to + / - 15mm
- 5 Power transmission with (steel reinforced) toothed belt
- 6 Self-teaching microprocessor control system installed in protective housing, with automatic adjustment for optimum dynamic operating performance of door
 - Obstacle detection with automatic return mechanism
 - Motor locking pressure: 40 N
 - Dynamic power limitation
 - LED-type function and error indicators
 - Prioritised fulfillment of operating commands
 - Weight and path measurement
 - Testing of safety and security elements
 - End-point positioning
 - Diagnostics enabled
- 7 Simple adjustment of the folldoor functions via the LED display D-Bedix:Mode / Program control:
 - Closing speed
 - Opening speed
 - Hold-open time
 - Reduced opening
 - Mode positions: Auto/Lock/Open/Manual/Exit
- 8 Programmable with Bluetooth option: Numerous operational characteristics and diagnostic settings can be achieved by our qualified service technicians to meet specific site requirements.
- 9 Electric Locking / Failsafe Backup Battery
 - In auto operation will provide up to 1/2 hour of continuous operation and fail open on battery expiration
 - In lock will provide up to 200 operations of unlock-open-close-lock or up to 3 days of secure locking with wakeup and unlock upon "key command". Lock is selectable failsafe or fail-secure
 - It is recommended that the battery be replaced every 2 years

Technical Specifications

Max. opening speed	0.8 m/s (adjustable)
Max. closing speed	0.8 m/s (mass-dependent, adjustable)
Hold-open time, day: adjustable time	0-45 s (adjustable)
until the door closes	
Mains power connection	230VAC, 50Hz
Stat. drive power	Max. 150N
Protection rating	IP23
Power consumption	280W
Ambient temperature	-15°C to +50°C
Frame size	140mmH x 165mmD

Range of Application

	Bi- parting	Single
Clearance opening width	800 ... 3000mm	700 ... 2000mm
Clearance height	2024 - 3100mm	
Max. door weight	2 x 150kg	1 x 200 kg
Minimal drive case length	2 x opening width + 100mm	
Gilgen door systems, tested to DIN 18650 standards PSX		

SLX300 drive unit: Various door leaf options are available.

