



Gilgen FD10 – Swing Door Operator

Specification:

The automatic Gilgen FD10 Swing door operators as supplied by Access Entry Pty are to be electrically approved for 230/240v. The single/double swing operators are to be housed in a natural anodized housing and cover of dimensions being Height 70mm x Depth 125mm x Width 730mm. The said operators are to be supplied by an Australian Owned and Operated Company and must comply with all BCA requirements for automatic door operators.

The equipment shall incorporate the following features:

- **Operation:** Door weight up to 150kg internal and external door operator continuous duty with manual operation with and without mains power. Suitable for both hinge and pivot type doors.
- **Mounting:** Bulkhead/Transom/Structural plate for operator fixing (By Others)
- **Arm Configuration:** Slide arm for both outward/inward opening or Push arm for outward opening
- **Opening Function:** 24V DC motor or manual override adjustable back check, drive has built- in travel stop.
- **Closing Function:** Controlled spring- actuation closure with motor assistance
- **Push & Go:** Standard, with auto spring powered close.
- **Opening Angle:** Max 105 deg.
- **Opening & Closing Speed:** Max 40/s
- **Power Source:** Solid 230v AC 50Hz 10a, Rated power 100W.
- **Control Circuit:** Solid state integrated circuit with lock output.
- **Interface Options:** Fire alarm, building management and security system interface.
- **Control Functions:** SK4- four position security switch (can be master keyed by client) or M4 rotary switch
- **Actuation Options:** Radar motion Eagle5 Sensor, Magic Switch/no touch pads, push button etc.
- **Safety option:** Eye tech active & passive infrared presence sensing system mounted on door leaf.
- **Locking:**
 - a. Manual locking (by door manufacturer)
 - b. Electric Strike & Emergency egress push button (by security)
 - c. Magnetic locks & Emergency egress push button for Inverse units (by security)
- **Special Entry**
 - a. Card reader or Swipe Care (by security)
 - b. SK2 switch for entry to match existing master keyed system. (can be master keyed by client)
 - c. Access Entry Privacy Kit with LED status indicator (DDA)
- **Fire Alarm:** Cabling provided by fire contractor. (1 set of open contacts voltage free)
- **Security & Remote Cabling:** Cabling by nominated security contractor. (0.2mm 8 core)

Warranties: The Gilgen FD10 Swing Door Operator is to be covered by a two (2) year parts guarantee and a twelve (12) months labour warranty.

Maintenance: The operator is to be safety inspected and maintained in accordance with AS5007-2007, i.e. three periodic log book entries per annum, by qualified technicians. Contact 1300 445 436 for safety/service program

HEAD OFFICE

Victoria
10 Network Dve
Carrum Downs 3201
P 03 8773 4200

NSW
5 Watson Rd
Padstow 2211
P 02 9973 6740

Queensland
14/37 Blanck St
Ormeau 4208
P 07 5551 6900

Access Entry Pty Ltd

ABN 84 602 327 024

24HR Service: 1300 445 436

Fax: 03 8773 4299

sales@accessentry.com.au

www.accessentry.com.au