



Product Name: Eco Bright White Elastomeric topcoat

Manufacture: SBH seal
1027 Autoroute 440 Ouest
Laval, QC H7L3W3 Canada

Product Description:

100% Acrylic elastomeric cool roof coating. The coating is designed to provide superior adherence to multiple surfaces, especially SBH seal Asphalt Emulsion Products.

Uses: This high-performance coating will protect the underlying roof system will maintaining excellent cold weather flexibility and additionally reduce roof temperatures. The coating has excellent flexibility, resists cracking and peeling, resists microbial/mildew growth, and provides a protective barrier which reflects the sun's heat and destructive UV rays.

Packaging: 5-gal bucket, 55-gal drum

Approx. Coverage: 1-1.5 gals per 100sqft, per application

Shelf Life: 2 years

Cautions: See SDS

Specifications: Meets ASTM D6083

Weight Per Gallon (lbs): 12.0-12.1

PH: >9

VOC: <30gr/L

Solids: Weight: 67%; Volume: 51%

Viscosity (Stormer): 105KU; Brookfield: 20,000cps

Initial Elongation Break: >200%, Final (1000h Accelerated Weathering): >175%

Tensile Strength: >265psi

Reflectivity: >85%

Permeance (perms): 20

Water Swelling (% mass): 4

Low Temperature Flexibility: PASS

Fungi Resistance: PASS(0)

Tear Resistance (lbf/in): >79

Wet adhesion (pli): Mod Bitumen: 4, SPUF: 3; Concrete: 5; Galvanized: 3

Technical Literature: Please visit Sbhseal.com

Caution: avoiding excessive rolling. For best protection, a second application is required at the same rate as soon as the first coat is thoroughly dry and firm enough to take foot traffic without damage. It is important to apply the second coat at opposite-right angles (perpendicular) to the first. **DO NOT** apply if temperature is below 50° f or above 110°f. **DO NOT** apply if heavy dew or rain is expected within 24 - 48 hours.

Availability and cost: Available worldwide all year. Please visit sbhseal.com to consult your local sales representative

Warranty/Maintenance: Please visit sbhseal.com for the latest updated warranty requirements and maintenance instructions.

Technical services: Please visit sbhseal.com for technical services nearest to your location