

DUO / POST TOP AREA LUMINAIRE



TECHNICAL DATA

• Luminaire source	LED SMD
• Luminaire system wattage*	40W ~ 100W
• Luminaire luminous flux*	4800lm ~ 12000lm
• Luminaire efficacy (avg.)	120lm/W (5000K)
• Correlated colour temperature*	5000K, other CCT on request
• Colour rendering index	Ra≥70, Ra≥80 on request
• Beam	Type V optic, others on request
• Service lifetime*	>60,000h L70/B10 (50°C)
• Ingress protection/resistance	IP66 / IK08
• Power factor	≥0.92
• Operating voltage	100-240V AC, 50/60Hz
• Operating temperature	-30°~50°C
• Protection class	I
• Finish	Grey (RAL9006), black (RAL9017) housing
• Construction	Aluminium, stainless steel, tempered glass
• Mounting	Pole spigot mount
• Warranty*	5 years
• Surge protection	6kV
• Luminaire termination	Pre-wired 3-core flex
• Lighting control	Non dimmable ECG standard
• Luminaire weight	8.7Kg~9.0Kg
• Spigot adaptor	Ø76mm standard, others on request

ORDER DATA

Model	System wattage	Colour temperature
DUO-40W	40W	5000K
DUO-60W	60W	5000K
DUO-75W	75W	5000K
DUO-100W	100W	5000K

Specify **-GRY** for grey finish; **-BLK** for black finish

FEATURES

- High luminous efficacy 120lm/W
- Robust construction, high impact resistance and corrosion resistant treated
- Inbuilt surge protection
- Simplistic architectural design

OPTIONS/ACCESSORIES

- Ø76mm spigot standard, Ø60mm optional
- Grey and black finish options
- Ra≥80 on request

