


## QUADRA / SHOPLIGHT LUMINAIRE



### TECHNICAL DATA

• Luminaire source	LED SMD
• Luminaire system wattage*	40W ~ 60W
• Luminaire luminous flux*	4400lm ~ 6600lm
• Luminaire efficacy (avg.)	110lm/W (4000K)
• Correlated colour temperature*	3000K/4000K/5700K switchable
• Colour rendering index	Ra≥80
• Chromaticity tolerance	4 MacAdam, initial
• Beam	90°
• Service lifetime*	>50,000h L70/B10
• Ingress protection	IP20
• Power factor	≥0.90
• Operating voltage	220-240V AC, 50/60Hz
• Operating temperature	-20°~45°C
• Protection class	III
• Finish	White trim (RAL9016)
• Construction	Aluminium housing, polycarbonate
• Mounting	Ceiling recessed
• Warranty*	5 years
• Luminaire termination	Pre-wired flex and plug
• Lighting control	TRIDONIC non dimmable ECG standard; TRIDONIC DALI/DSI dimming on request

### ORDER DATA

Model	System wattage	Colour temperature
QUADRA-40W	40W	3000K/4000K/5700K
QUADRA-60W	60W	3000K/4000K/5700K

*Specify -D for DALI/DSI dimming*

### FEATURES

- High efficacy, ideal conventional luminaire replacement upto 150W MH
- Switchable colour temperature via fitting; 3000K, 4000K, 5700K
- Superior thermal capacity
- 65° tilt adjustability

### OPTIONS/ACCESSORIES

- TRIDONIC DALI/DSI dimming on request

