

## GEOMETRIE CUBE GRAVEL-BIKE NUROAD C:62 Race

RAHMEN	C:62 Advanced Twin Mold, Internal Cable Routing, Flat Mount Disc, Fender/Rack & Kickstand Option, 12x142mm, AXH
GRÖSSE	XS (50cm), S (53cm), M (56cm), L (58cm), XL (61cm)
GABEL	CUBE C:62 Technology, 1 1/8" - 1 1/4" Tapered, Flat Mount Disc, Fender & Lowrider Mounts, Internal Light Cable Option, 12x100mm
BREMSANLAGE	Shimano BR-RX810, Hydr. Disc Brake, Flat Mount (160/160)
SCHALTWERK	Shimano GRX RD-RX810, Direct Mount, 11-Speed
UMWERFER	Shimano GRX FD-R810
SCHALT-/ BREMSGRIFFE	Shimano GRX ST-RX810
KURBELGARNITUR	Shimano GRX FC-RX810, 11-Speed, 48x31T
KASSETTE	Shimano Ultegra CS-R8000, 11-32T
KETTE	Shimano CN-HG700-11
LAUFRADSATZ	Newmen Evolution SL X.R.25
REIFEN	Schwalbe G-One Allround, Kevlar, 40-622
VORBAU	CUBE Performance Stem SL, 31.8mm
LENKER	Easton EC70 AX Gravel, Carbon
LENKERBAND	CUBE Grip Control
SATTELSTÜTZE	Newmen Advanced, Carbon, 27.2mm
SATTELKLEMME	CUBE Semi-Integrated
SATTEL	Natural Fit Nuance Lite
STEUERSATZ	VP, Top Integrated 1 1/8", Bottom Integrated 1 1/4"
GEWICHT	8,5 kg
FARBE	green´n´lime

GRÖSSE	XS-50cm	S-53cm	M-56cm	L-58cm	XL-61cm
SITZROHR	470	500	530	550	580
SITZROHR MITTE-MITTE	429	459	488	509	540
OBERROHR HORIZONTAL	518	537	560	575	592
SITZWINKEL	75,2	74,5	73,5	73	73
STEUERROHRWINKEL	69	70	71,5	72	72,5
KETTENSTREBEN	439,5	439,5	439,5	439,5	439,5
STEUERROHR	102	124	154	174	197
RADSTAND	1041	1041	1041	1046	1058
TRETLAGERHÖHE ZUR NABENACHSE	-70	-70	-70	-70	-70
ÜBERSTANDSHÖHE	750,8	779	810	830	856
REACH	380,7	386	389	392	401,6
STACK	519,6	544	578	599	622,6
LAUFRADGRÖSSE	28	28	28	28	28

