

GEOMETRIE CUBE KATHMANDU HYBRID PRO 625

RAHMEN	Aluminium Superlite, Gravity Casting Technology, Efficient Comfort Geometry, Tapered Headtube, Full Integrated Battery, Integrated Carrier 2.0
GRÖSSE	S (50cm), M (54cm), L (58cm), XL (62cm);
GABEL	SR Suntour XCR32 LO-R Air, 100mm, Lockout
MOTOR	Bosch Drive Unit Performance CX Generation 4 (85Nm) Cruise (250Watt)
AKKU	Bosch Power Tube 625
DISPLAY	Bosch Intuvia
LADEGERÄT	Bosch 2A
BREMSANLAGE	Shimano BR-MT200, Hydr. Disc Brake (180/180)
SCHALTWERK	Shimano Deore RD-M5120-SGS, 10-Speed
SCHALTHEBEL	Shimano Deore SL-M4100, Rapidfire Plus
KURBELGARNITUR	ACID E-Crank, 38T (175mm // EE: 170mm)
KASSETTE	Shimano Deore CS-M4100, 11-46T
KETTE	KMC X10
VORDERRAD NABE	Shimano HB-TX505, QR, Centerlock
HINTERRAD NABE	Shimano FH-TX505, QR, Centerlock
FELGEN	CUBE EX23, 36H, Disc, Tubeless Ready
REIFEN	Schwalbe Big Ben, Performance, 55-622
VORBAU	Satori Up2 Plus, 31.8mm, Adjustable
LENKER	CUBE Comfort Trail Bar, 700mm
GRIFFE	Natural Fit Comfort
SATTELSTÜTZE	CUBE Suspension Seatpost HD, 30.9mm
SATTELKLEMME	CUBE Varioclose, 34.9mm
SATTEL	Natural Fit Sequence Comfort
STEUERSATZ	M, L: ACROS AZF-1039, 1 1/8" straight, Top Zero-Stack 1 1/8" (ZS 44mm), Bottom Zero-Stack 1 1/2" (ZS 56mm) // EE: ACROS AZX-1041, BlockLock 135°, 1 1/8" straight, Top Zero-Stack 1 1/8" (ZS 44mm), Bottom Zero-Stack 1 1/2" (ZS 56mm)
PEDALE	ACID PP Trekking
SCHEINWERFER	CUBE Shiny 50 Lux, 12V, DC
RÜCKLICHT	CUBE Edge IC 2.0 Rear LED, 12V, DC
STÄNDER	CUBEstand Cmpt
SCHUTZBLECHE	ACID 65 BB-Mount
GLOCKE	Mini Bell
GEPÄCKTRÄGER	CUBE Integrated Carrier 2.0, CUBE Adapter Compatible, SnapIt Compatible
GEWICHT	25,7 kg
FARBE	black'n'blue

GRÖSSE	S-50cm	M-54cm	L-58cm	XL-62cm
SITZROHR	480	520	560	600
SITZROHR MITTE-MITTE	435	473	513	553
OBERROHR HORIZONTAL	590	600	610	620
SITZWINKEL	74	74	74	74
STEUERROHRWINKEL	68,5	68,5	68,5	68,5
KETTENSTREBEN	460	460	460	460
STEUERROHR	105	114	133	154
RADSTAND	1144	1155	1165	1177
TRETLAGERHÖHE ZUR NABENACHSE	-68	-68	-68	-68
ÜBERSTANDSHÖHE	808	835	866	899
REACH	415	423	427	430
STACK	624	632	650	669
LAUFRADGRÖSSE	28	28	28	28

