

88.9mm Drill Rod Specification Table

Diameter	Thread	Wall Thickness	Length	Weight kg	Joint Bore	Spanner A/F	Extended Joint Effective Lengths
A		B	C		D	E	F
88.9	2 3/8" Reg	4.5	3000	34.5	25	76	
88.9	2 3/8" Reg	4.5	2000	25.2	25	76	
88.9	2 3/8" Reg	4.5	1500	20.5	25	76	
88.9	2 3/8" Reg	4.5	1000	16	25	76	
88.9	2 3/8" Reg	6.35	3000	43	25	76	
88.9	2 3/8" Reg	6.35	2000	31	25	76	
88.9	2 3/8" Reg	6.35	1500	25	25	76	
88.9	2 3/8" Reg	6.35	1000	19	25	76	
88.9	2 7/8" Reg	6.35	3000	44	31.75	76	
88.9	2 7/8" Reg	6.35	2000	32	31.75	76	
88.9	2 7/8" Reg	6.35	1500	26	31.75	76	
88.9	2 7/8" Reg	6.35	1000	20	31.75	76	
88.9	2 3/8" IF	6.35	3000	44	44.5	76	
88.9	2 3/8" IF	6.35	2000	32	44.5	76	
88.9	2 3/8" IF	6.35	1500	26	44.5	76	
88.9	2 3/8" IF	6.35	1000	20	44.5	76	
88.9 (Ext)	2 3/8" Reg	6.35	5000	75	25	No Flats - T/Joints 250 mm Eff each end	
88.9 (Ext)	2 3/8" Reg	6.35	4000	61	25	No Flats - T/Joints 250 mm Eff each end	
88.9 (Ext)	2 3/8" Reg	6.35	3000	47	25	No Flats - T/Joints 250 mm Eff each end	
88.9 (Ext)	2 3/8" Reg	6.35	1500	29	25	No Flats - T/Joints 250 mm Eff each end	
88.9 (Ext)	2 3/8" Reg	9.52	5000	102	25	No Flats - T/Joints 250 mm Eff each end	
88.9 (Ext)	2 3/8" Reg	9.52	4000	83	25	No Flats - T/Joints 250 mm Eff each end	
88.9 (Ext)	2 3/8" Reg	9.52	3000	64	25	No Flats - T/Joints 250 mm Eff each end	
88.9 (Ext)	2 3/8" Reg	9.52	1500	37	25	No Flats - T/Joints 250 mm Eff each end	