

76mm Drill Rod Specification Table

Diameter	Thread	Wall Thickness	Length	Weight kg	Joint Bore	Spanner A/F	Extended Joint Effective Lengths
A		B	C		D	E	F
76	2 3/8" Reg	4	3000	24	25	64	
76	2 3/8" Reg	4	2000	19	25	64	
76	2 3/8" Reg	4	1500	16	25	64	
76	2 3/8" Reg	4	1000	12	25	64	

76	2 3/8" Reg	6.35	3000	39	25	64	
76	2 3/8" Reg	6.35	2000	28	25	64	
76	2 3/8" Reg	6.35	1500	23	25	64	
76	2 3/8" Reg	6.35	1000	17	25	64	

76 (Ext)	2 3/8" Reg	4	4000	53	25	No Flats - T/Joints 200mm Eff each end	
76 (Ext)	2 3/8" Reg	4	3000	41	25	No Flats - T/Joints 200mm Eff each end	
76 (Ext)	2 3/8" Reg	4	2000	29	25	No Flats - T/Joints 200mm Eff each end	
76 (Ext)	2 3/8" Reg	4	1500	24	25	No Flats - T/Joints 200mm Eff each end	

76 (Ext)	2 3/8" Reg	6.35	4000	53	25	No Flats - T/Joints 200mm Eff each end	
76 (Ext)	2 3/8" Reg	6.35	3000	41	25	No Flats - T/Joints 200mm Eff each end	
76 (Ext)	2 3/8" Reg	6.35	2000	29	25	No Flats - T/Joints 200mm Eff each end	
76 (Ext)	2 3/8" Reg	6.35	1500	24	25	No Flats - T/Joints 200mm Eff each end	