Generator Model APK-K14(230)

Generator Rating		Prime	Standby
Power	kVA	13	14
Power	kW	10	11
Current	A	55	60
Standard Voltage	V	230 Single Phase	
Revolution Per Minute	R.P.M.	1500	
Rated at power Factor	Cos Phi	0.8	

Standard Features

- 4 Stroke, 1500 RPM, water-cooled heavy-duty diesel engine
- Automatic or manual start with built in protection system
- Flexible oil pipes and oil drain valve
- Pre-heater and water heater
- Lubrication oil and anti-freeze
- 4 Pole, synchro type, single bearing, brushless alternator
- Fully rated batteries and cables
- Base or roof lifting points
- Bunded base fuel tank
- Industrial rated silencer
- Electronic battery charger
- EPO (Emergency Push Off)
- 3 or 4 pole output breaker
- Electrical wiring diagram
- User manual and operating manual

Optional Features

- 3 or 4 pole Automatic Transfer panel (ATS) electrically and mechanically interlocked
- Remote alarm volt free contacts
- Remote monitoring (RS232 / RS485)
- G99 Operation
- Battery isolator
- Canopy colour
- Low noise canopy down to 65dBA
- Parallel operation
- Residential silencer
- Air flow variations
- Extended fuel tank
- Remote fuel tank with/without automatic day tank fill system

Additional Services Available

- Site surveys
- Hiab delivery
- Generator positioning
- Air handling and exhaust extension supply and installation
- Commissioning
- Maintenance contract

Prime Power: Supplying of electrical power at variable load for an unlimited number of hours in the event of normal utility power failure according to ISO85281. 10% over load capability is available.

Stand by Power: Supplying of electrical power at variable load, in the event of normal utility power failure according to ISO85281. This rating is maximum power, no overload capability is available.

ABILITY POWER LIMITED
Secure your future Power
Suppliers & Servicing of Generators, UPS & other power products
Tel +44 (0) 1437 766 984
Email sales@abilitypower.co.uk
www.abilitypower.co.uk

Engine Specification		
Brand		KOHLER
Model		LDW1603
Engine Power Stand By	(kWm / hp)	15.5/21
Revolution Per Minute	(R.P.M)	1500
Total Displacement	(L)	1.65
Cylinders Orientation		3 Vertical inline
Bore x Stroke	(mm x mm)	88 x 90.4
Compression Orientation		22:1
Governor Type		Mechanical
Aspiration System		Natural
Injection		indirect
Cooling		Water Cooled
Electrical System	(VDC)	12
Lub-Oil Capacity	(L)	4.4
Engine Coolant Capacity	(L)	5.8
Fuel Tank Capacity	(L)	51
Maximum Exhaust Temperature	(°C)	460
Maximum Exhaust Gas Flow	(m3/min)	5.9
Maximum Allowed Back Pressure	(kPa)	6
Cooling Air Flow	(m3/sec)	-
Fuel Consumption 50%	(L/h)	2.7
Fuel Consumption 75%	(L/h)	3.7
Fuel Consumption 100%	(L/h)	4.9

Alternator Specification		
Standard Voltage	(V)	230
Frequency	(Hz)	50
Stationary Voltage Regulation	(±)	1%
Short Circuit Current		>300%
Insulation		H/H
Protection		IP 23
Efficiency	(%)	81.7
Overloading		110% For 1 Hour
Power Factor	(cos Phi)	0.8
Total Harmonic Distortion rate		THF <2%
Connection Type		Delta
Number of poles		4
Number of Bearings		Single

ABILITY POWER
Secure your future Power
Supplying & Servicing of Generators, UPS & other power products
Tel: +44 (0)1437 766984
Email: sales@abilitypower.co.uk
www.abilitypower.co.uk

Dimensions with canopy		
Length (L)	mm	1385
Height (H)	mm	1190
Width (W)	mm	855
Wet Weight	kg	452
Fuel Tank Capacity	L	53

Dimensions without Canopy		
Length (L)	mm	1385
Height (H)	mm	1190
Width (W)	mm	855
Wet Weight	kg	370
Fuel Tank Capacity	L	53



Please note above images are an example actual unit may vary

Standard D500 Control Panel Features

- Diesel and gas genset support
- 400Hz operation support
- 400 event logs, full snapshot
- All parameters front panel editable
- 3 level configuration password
- 128x64 graphical LCD display
- Downloadable language
- Waveform display of V & I
- Harmonic analysis of V & I
- Synchro scope & check synch
- Allows closed transfers
- 16Amp MCB & GCB outputs
- 8 configurable digital outputs
- Outputs expandable to 40
- 4 configurable analogue inputs
- Both CANBUS-J1939 & MPU
- 3 configurable service alarms
- Multiple nominal conditions
- Multiple automatic exerciser
- Weekly operation schedule
- Dual mutual standby with equal aging of gensets
- Manual "speed fine adjust" on selected ECUs
- Automatic fuel pump control
- Disable protections feature
- Excess power protection
- Reverse power protection
- Overload IDMT protection
- Load shedding, dummy load
- Multiple load management
- Current unbalance protection
- Voltage unbalance protection
- Fuel filing & fuel theft alarms
- Battery back-up real time clock
- Idle speed control
- Battery charge run enabled
- Contactor & MCB drive
- 4 quadrant genset power counters
- Mains power counters
- Fuel filing counter
- Fuel consumption counter
- Modem & Ethernet diagnostics configurable through USB, RS-485, Ethernet and GPRS
- Free configuration program
- Allows SMS controls
- Ready for central monitoring
- Ethernet and GPRS
- Mobile genset support
- Automatic GSM geo-location
- GPS connectivity (USB & RS232)
- Dynamic DNS support
- Easy USB firmware upgrade
- IP65 rating with standard gasket

Secure your future Power
Supplying & Servicing of Generators, UPS & other power products
+44 (0) 1437 766 984
sales@abilitypower.co.uk
www.abilitypower.co.uk