|--|

Latch Format	Mechanical Mortise	Backset 55mm
	Tubular Single Latch	Backset 60mm/70mm/127mm
Handing	Reversible for both sides of the door.	
Door Thickness	35mm - 80mm	
Installation	support.goki.travel	
Dressing-plate Option	8" x 1/4", 0.06" Thick / 203.2 x 6.4 mm, 1.5mm Thick	
Strike Plate	ANSI 4-7/8" x 1-1/4" / 123.8 x 31.75 mm	
<u>Features</u>		
Credentials	Smartphone - iOS/Android/Web, NFC Card/Tag/Band, DoorCode, Mechanical Key	
Users	1500	
Management	Spaces Staff App & Cloud-based Staff Dashboard	

Communication

Communication	
Wireless	Bluetooth Low Energy 5.0 (BLE), Near Field Communication (NFC), Web (Via built in wi-fi module and/or GokiAir Gateways)
NFC Type	MIFARE
NFC Frequency	13.56 MHz
Devices	iOS, Watch OS, Android, Web App (Chrome Browser)
Power	
Supply	10,000 MaH Lithium Ion
Status	Real time status on Spaces Staff App & Dashboard. Active Notifications
Charge	Rechargeable via USB-C
Jumpstart	Power externally via USB-C
Environmental	
Operating temp	Interior: -20°C to 54°C

	Operating Humidity	0-95% relative humidity, non-co	ondensing
--	--------------------	---------------------------------	-----------

Weather Resistance Disc: IP65, Exterior/Interior Assemblies: IP55