

MOTORSPORT COUPLINGS



W900 Series Coupling



Ferrules Available in Weld or Swage

THE W900 SERIES COUPLING

The W900 series is qualified for use in applications demanding high performance and provides a reliable, lightweight and flexible solution for fuel, oil, water and gas systems. The connector utilises standard 'O' rings and can be installed and removed quickly and simply using one hand.

Connectors and ferrules are stocked within USA & Europe in sizes ranging from -8 to -64 (0.5" to 4.0") in Aluminium, CRES and Titanium.

** Plugs, caps and adaptors are available upon request.

AUTHORIZED STOCKING/DISTRIBUTOR

- Orkal carries all sizes in inventory ready for same day shipment
- Orkal can fix pricing for multi year blanket Agreements
- Schedule deliveries over multi year Agreements
- Orkal stocks all couplings in New York and Germany warehouses
- All Couplings come with MFG COC and are inspected by Orkal

Labor Cost Savings, Increase Throughput, Prevent Repetitive Motion Injury, Eliminate FOD

Contact Us

Orkal
333 Westbury Avenue
Carle Place NY 11514
516 333 2121
orkal@orkal.com
www.orkal.com

BENEFITS TO YOU

- One-handed/Blind installation
- Easy to close without special tools or tapes
- Locks closed
- Keep hands free
- Reusable
- Lightweight
- Robust Aerospace design
- Performance validated through testing and in field use
- Availabe with and without bonding tabs



		CONNECTOR		FERRULE (WELD)		SEAL SIZE 1 per ferrule (Not supplied)
TUBE	SIZE	ALUMINIUM	CRES	ALUMINIUM	CRES	
O/D	CODE	Part Number	Part	Part Number	Part	per AS568
			Number		Number	
0.5"	8	W991-8DE	W991-8CE	W903B8D	W903B8C	-015
0.625"	10	W991-10DE	W991-10CE	W903B10D	W903B10C	-017
0.75"	12	W991-12DE	W991-12CE	W903B12D	W903B12C	-117
1.0"	16	W991-16DE	W991-16CE	W903B16D	W903B16C	-214
1.25"	20	W991-20DE	W991-20CE	W903B20D	W903B20C	-218
1.5"	24	W991-24DE	W991-24CE	W903B24D	W903B24C	-222
1.75"	28	W991-28DE	W991-28CE	W903B28D	W90328C	-224
2.0"	32	W991-32DE	W991-32CE	W903B32D	W903B32C	-226
2.5"	40	W991-40DE	W991-40CE	W903B40D	W903B40C	-230
3.0"	48	W991-48DE	W991-48CE	W903B48D	W903B48C	-234
3.5"	56	W991-56DE	W991-56DE	W903B56D	W903B56C	-238
4.0"	64	W991-64DE	W991-64CE	W903B64D	W903B64C	-242
4.5"	72	W991-72DE	W991-72DE	W903B72D	W903B72D	-246
** Use W991M to order without bonding tabs						

