

Section 1-Chemical Product and Company Identification

Company Information:

PremierRepak Inc. Phone: (708) 444-2688 8351 W. 185th Street Fax: (708) 429-4280

Tinley Park, IL 60487 www.premierrepak.com

InfoTrac 24-hour Emergency Phone Number: 1 (800) 535-5053

InfoTrac Contract Number: 105384

Product Information:

Substance/Mixture: Substance

Substance name: Hexamethyldisiloxane: CAS Number: 107-46-0

Chemical nature: Silicone

Recommended use: Intermediate, Cosmetics, Solvent, Laboratory chemicals

Section 2-Hazard Identification

GHS Classification: Flammable liquids: Category 2

GHS Label element:



Signal Word: DANGER

Hazard Statements:

H225: Highly flammable liquid and vapor.

Precautionary Statements:

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Responses:

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



Storage:

P403 + P235: Store in a well-ventilated place. Keep cool.

Disposal:

P501: Dispose of contents/container to an approved waste disposal plant.

Other hazards:

Vapors may form explosive mixture with air. Static-accumulating flammable liquid.

Section 3-Composition and Information on Ingredients

Hazardous Ingredients:

Common Name	C.A.S. No.	Wt. %	
Hexamethyldisiloxane	107-46-0	>= 90 - <= 100	

Section 4 – First Aid Measures

If inhaled: Remove to fresh air. Get medical attention if symptoms occur.

In case of skin contact: Wash with water and soap as a precaution. Get medical attention if symptoms occur. Wash clothing before reuse.

In case of eye contact: Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.

If swallowed: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed: None known

Protection of first-aiders: No special precautions are necessary for first aid responders.

Notes to physician: Treat symptomatically and supportively.

Section 5- Firefighting Measures

Suitable extinguishing media: Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO2)

Unsuitable extinguishing media: High volume water jet

Specific hazards during firefighting: Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.

Hazardous combustion products: Carbon oxides, Silicon oxides, Formaldehyde.

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



Specific extinguishing methods: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for fire fighters: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Remove all sources of ignition. Ventilate the area. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions:

Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained. Prevent spreading over a wide area (e.g. by containment or oil barriers).

Methods and materials for containment and cleaning up:

Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

Section 7- Handling and Storage

Technical measures:

Ensure all equipment is electrically grounded before beginning transfer operations. This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity; it is necessary to provide an inert gas purge before beginning transfer operations. Restrict flow velocity in order to reduce the accumulation of static electricity.

Local/Total ventilation:

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.

Advice on safe handling:

Avoid inhalation of vapor or mist. Handle in accordance with good industrial hygiene and safety practice. Nonsparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



Conditions for safe storage:

Keep in properly labeled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Materials to avoid:

Do not store with the following product types:

Strong oxidizing agents

Organic peroxides

Flammable solids

Pyrophoric liquids

Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit flammable gases

Explosives

Gases

Section 8- Exposure Controls and Personal Protection

Hazardous Component with workplace control parameters:

	Common Name	C.A.S. No.	Value type (Form of exposure)	Control parameters Permissible Conc.	Basis
	Hexamethyldisiloxane	107-46-0	TWA	200 PPM	Supplier Reference
Hazardous Component without workplace control parameters:					
	Common Name		C.A.S. N	<u>o.</u>	
	None				
Occupational exposure limits of decomposition products:					

		value type	Control parameters	
Common Name	C.A.S. No.	(Form of exposure)	Permissible Conc.	Basis
		• •		

NONE

Engineering measures:

Processing may form hazardous compounds (see section 10). Minimize workplace exposure concentrations. Use only in an area equipped with explosion proof exhaust ventilation. Use with local exhaust ventilation.

Personal protective equipment:

Respiratory protection: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection:

Material: Antistatic gloves

Material: Flame-retardant gloves

Remarks: Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Wash hands before breaks and at the end of workday.

Eye protection: Wear the following personal protective equipment: Safety goggles.

Skin and body protection:

Wear the following personal protective equipment:

Flame retardant antistatic protective clothing. Select appropriate protective clothing based on chemical resistance data and assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures:

Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the PremierRepak customer service group.

Section 9- Physical/Chemical Characteristics

Odor: Characteristic Appearance: Liquid Odor Threshold: No data available Color: Colorless

Freezing/Melting Point: No data available.

Initial Boiling Point and Boiling Point Range: 100 degrees Celsius

Vapor Pressure: 42 hPa

Vapor Density: No data available. Solubility in Water: No data available.

pH: No data available.

Volatile Content: Not determined.

Flash Point: -3.3 degrees Celsius: Method: Pensky-Martens closed cup

Auto ignition Temperature: 352 degrees Celsius

Flammability (solid, gas): Not applicable Evaporation rate: No data available **Upper explosion limit:** 14.65% (V) Lower explosion limit: 1.5% (V)

Partition coefficient: noctanol/water: No data available **Decomposition temperature**: No data available

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



Viscosity, kinematic: 0.65 mm2/s Explosive properties: Not explosive

Oxidizing properties: The substance or mixture is not classified as oxidizing.

Molecular weight: No data available

Relative Density: 0.76

Section 10- Stability and Reactivity

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions:

Highly flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid:

Handling operations that can promote accumulation of static charges. Heat, flames and sparks.

Incompatible materials: Oxidizing agents

Hazardous decomposition products:

Thermal decomposition: Formaldehyde

Section 11– Toxicological Information

Information on likely routes of exposure:

Skin contact Ingestion Eye contact Inhalation

Acute toxicity:

Not classified based on available information.

Product:

Oral:

Acute toxicity: LD50 (Rat): > 16 mg/kg

Assessment: The substance or mixture has no acute oral toxicity

Remarks: Based on test data.

Inhalation:

Acute toxicity: LC50 (Rat): > 15956 ppm

Exposure time: 4 h Test atmosphere: vapor

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



Assessment: The substance or mixture has no acute inhalation toxicity

Remarks: Based on test data

Dermal:

Acute toxicity: LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal toxicity

Remarks: Based on test data.

Ingredients:

Hexamethyldisiloxane:

Oral:

Acute toxicity: LD50 (Rat): > 16 mg/kg

Assessment: The substance or mixture has no acute oral toxicity

Remarks: Based on test data.

Inhalation:

Acute toxicity: LC50 (Rat): > 15956 ppm

Exposure time: 4 h Test atmosphere: vapor

Assessment: The substance or mixture has no acute inhalation toxicity

Remarks: Based on test data

Dermal:

Acute toxicity: LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal toxicity

Remarks: Based on test data.

Skin corrosion/irritation:

Not classified based on available information.

Product:

Species: Rabbit Result: No skin irritation Remarks: Based on test data.

Ingredients:

Hexamethyldisiloxane:

Species: Rabbit Result: No skin irritation Remarks: Based on test data.

Serious eye damage/eye irritation:

Not classified based on available information.

Product:

Species: Rabbit Result: No eye irritation

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



Remarks: Based on test data.

Ingredients:

Hexamethyldisiloxane:

Species: Rabbit
Result: No eye irritation
Remarks: Based on test data.

Respiratory or skin sensitization:

Skin sensitization: Not classified based on available information. **Respiratory sensitization:** Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization **Test Type:** Human repeat insult patch test (HRIPT)

Species: Humans

Remarks: Based on test data.

Ingredients:

Hexamethyldisiloxane:

Assessment: Does not cause skin sensitization **Test Type:** Human repeat insult patch test (HRIPT)

Species: Humans

Remarks: Based on test data.

Germ cell mutagenicity:

Not classified based on available information.

Product:

Genotoxicity in vitro:

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on test data

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on test data

Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: negative

Remarks: Based on test data

Test Type: DNA damage and repair, unscheduled DNA

synthesis in mammalian cells (in vitro)

Result: negative

Remarks: Based on test data

Genotoxicity in vivo:

Test Type: Mutagenicity (in vivo mammalian bone-marrow

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29
Document: SDS-PRSF 0.65CST Revision #: 6



cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on test data

Germ cell mutagenicity Assessment: Animal testing did not show any mutagenic effects.

Ingredients:

Hexamethyldisiloxane:

Genotoxicity in vitro:

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on test data

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on test data

Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: negative

Remarks: Based on test data

Test Type: DNA damage and repair, unscheduled DNA

synthesis in mammalian cells (in vitro)

Result: negative

Remarks: Based on test data

Genotoxicity in vivo:

Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on test data

Germ cell mutagenicity Assessment: Animal testing did not show any mutagenic effects.

Carcinogenicity:

Not classified based on available information.

Product:

Application Route: Inhalation

Result: negative Species: Rats

Remarks: Based on test data

Carcinogenicity Assessment: Animal testing did not show any mutagenic effects.

Product: PR 0.65CST Silicone Fluid
Document: SDS-PRSF 0.65CST
Revision #: 6



Ingredients:

Hexamethyldisiloxane:

Application Route: Inhalation

Result: negative Species: Rats

Remarks: Based on test data

Carcinogenicity Assessment: Animal testing did not show any mutagenic effects.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity:

Not classified based on available information.

Product:

Effects on fertility:

Test Type: Two-generation reproduction toxicity study

Species: Rat, male and female **Application Route**: Inhalation (vapor)

Result: No effects on fertility **Remarks:** Based on test data

Effects on fetal development:

Test Type: Two-generation reproduction toxicity study

Species: Rat, male and female Application Route: Inhalation (vapor) Result: No effects on fetal development

Remarks: Based on test data

Reproductive Assessment: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

Ingredients:

Hexamethyldisiloxane:

Effects on fertility:

Test Type: Two-generation reproduction toxicity study

Species: Rat, male and female
Application Route: Inhalation (vapor)

Result: No effects on fertility Remarks: Based on test data

Effects on fetal development:

Product: PR 0.65CST Silicone Fluid

Document: SDS-PRSF 0.65CST

Revision #: 6



Test Type: Two-generation reproduction toxicity study

Species: Rat, male and female Application Route: Inhalation (vapor) Result: No effects on fetal development

Remarks: Based on test data

Reproductive Assessment: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

STOT-single exposure:

Not classified based on available information.

STOT-repeated exposure:

Not classified based on available information.

Product:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or

Routes of exposure: Skin contact

Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw

or less.

Ingredients:

Hexamethyldisiloxane:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw

or less.

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or

less.

Routes of exposure: Skin contact

Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw

or less.

Repeated dose toxicity:

Product:

Species: Rat

Routes of exposure: Ingestion Remarks: Based on test data

Species: Rat

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



Routes of exposure: Inhalation (vapor)
Remarks: Based on test data

Species: Rat

Routes of exposure: Skin Contact Remarks: Based on test data

Ingredients:

Hexamethyldisiloxane:

Species: Rat

Routes of exposure: Ingestion Remarks: Based on test data

Species: Rat

Routes of exposure: Inhalation (vapor)

Remarks: Based on test data

Species: Rat

Routes of exposure: Skin Contact Remarks: Based on test data

Aspiration toxicity:

Not classified based on available information.

Further information:

Ingredients:

Hexamethyldisiloxane:

Remarks: This material contains hexamethyldisiloxane (HMDS). Repeated inhalation exposure in rats to HMDS resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

Section 12 - Ecological Information

Ecotoxicity:

Ingredients:

Hexamethyldisiloxane:

Toxicity to fish:

LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.46 mg/l

Exposure time: 96 h

Remarks: Based on test data.

Toxicity to algae:

EC50: Selenastrum capricornutum (green algae)): > 0.55 mg/l

Exposure time: 96 h

Remarks: Based on test data. No toxicity at the limit of solubility.

Product: PR 0.65CST Silicone Fluid

Document: SDS-PRSF 0.65CST

Revision Date: 2018/10/29

Revision #: 6



Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity):

NOEC (Daphnia sp.): > 0.08 mg/l

Exposure time: 21 d

Remarks: Based on test data.

M-Factor (Acute aquatic toxicity): 1

Ecotoxicity Assessment:

Chronic Aquatic toxicity: Toxic to aquatic life with long lasting effect.

Persistence and degradability:

Ingredients:

Hexamethyldisiloxane:

Biodegradability:

Result: Not readily biodegradable.

Biodegradation: 20 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Stability in water:

Degradation half life: 116 h pH: 7 Method: OECD Test Guideline 111 Remarks: Based on test data

Bioaccumulative potential:

Ingredients:

Hexamethyldisiloxane:

Bioaccumulation:

Species: Cyprinus carpio (Carp) Bioconcentration factor: (BCF): 2,410

Concentration: 0.04 mg/l Remarks: Based on test data

Partition coefficient n- octanol/water: log Pow 5.06 (20 degrees Celsius)

Remarks: Based on test data

Mobility in soil: No data available

Other adverse effects: No data available

Section 13 – Disposal Considerations

Disposal methods:

Resource Conservation and Recovery Act (RCRA): When a decision is made to discard this material as supplied, it is classified as a RCRA hazardous waste.

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



Waste Code: D001: Ignitability

Waste from residues: Dispose of in accordance with local regulations.

Contaminated packaging:

Do not burn, or use a cutting torch on, the empty drum.

Dispose of as unused product.

Empty containers should be taken to an approved waste-handling site for recycling or disposal.

Section 14 – Transport Information

International Regulation:

UNRTDG:

UN number: UN 1993

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane)

Class: 3

Packing group: II

Labels: 3

IATA-DGR:

UN/ID No.: UN 1993

Proper shipping name: Flammable liquid, n.o.s. (Hexamethyldisiloxane)

Class: 3 Packing group: II

Labels: Flammable Liquids

Packing instruction (cargo aircraft): 364 Packing instruction (passenger aircraft): 353

IMDG-Code:

UN number: UN 1993

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane)

Class: 3 Packing group: II Labels: 3

EmS Code: F-E, S-E Marine pollutant: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

Not applicable for product as supplied.

Domestic regulation:

49 CFR:

UN/ID/NA number: UN 1993

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane)

Class: 3

Packing group: II

Labels: Flammable Liquid

ERG Code: 128

Marine pollutant: yes (Hexamethyldisiloxane)

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



Section 15- Hazard Classification

EPCRA (Emergency Planning and Community Right-to-Know):

CERCLA Reportable Quantity:

Component Name CAS Number Component RQ (lbs) Calculated product RQ(lbs)

NONE

SARA 304 Extremely Hazardous Substances Reportable Quantity:

Component Name CAS Number Component RQ (lbs) Calculated product RQ(lbs)

NONE

SARA 311/312 Hazards: Fire Hazard

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations:

California:

Warning: This product does NOT contain the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

Component Name CAS Number

NONE

State Right-To-Know:

CAS Number	Wt %	Component Name	State State
107-46-0	90 - 100 %	Hexamethyldisiloxane	New Jersey, Pennsylvania

The ingredients of this product are reported in the following inventories:

AICS: All ingredients listed or exempt.

DSL: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of

Chemical Substances.

NZIoC: All ingredients listed or exempt.

REACH: All ingredients (pre-) registered or exempt.

Product: PR 0.65CST Silicone Fluid

Document: SDS-PRSF 0.65CST

Revision Date: 2018/10/29

Revision #: 6

Page 15 of 17



IECSC: All ingredients listed or exempt.

ENCS/ISHL: All components are listed on ENCS/ISHL or exempted from inventory listing.

KECI: All ingredients listed, exempt or notified. PICCS: All ingredients listed or exempt. TCSI: All ingredients listed or exempt.

Section 16 - Other Information

Further information:

NFPA: HMIS III:

> Flammability: 3 Health: 0 Instability: 0

Special hazard: None Flammability: 3 Health: 0 Physical Hazard: 0

> 0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme. * = Chronic

Sources of key data used to compile the Material Safety Data Sheet:

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Full text of other abbreviations:

AICS = Australian Inventory of Chemical Substances ASTM = American Society for the Testing of Materials bw = body weight **CERCLA** = Comprehensive Environmental Response, Compensation, and Liability Act **CMR** = Carcinogen, Mutagen or Reproductive Toxicant DIN = Standard of the German Institute for Standardization DOT = Department of Transportation DSL = Domestic Substances List (Canada) ECx = Concentration associated with x% response EHS = Extremely Hazardous Substance ELx = Loading rate associated with x% response EmS = Emergency Schedule ENCS = Existing and New Chemical Substances (Japan) ErCx = Concentration associated with x% growth rate response ERG = Emergency Response Guide GHS = Global Harmonization System GLP = Good Laboratory Practice HMIS = Hazardous Material Identification System IARC = The International Agency for Research on Cancer IATA = International Air Transportation Association IBC = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk IC50 = Half maximal inhibitory concentration ICAO = International Civil Aviation Organization IECSC = Inventory of Existing Chemical Substances in China IMDG = International Maritime Dangerous Goods IMO = International Maritime Organization ISHL = Industrial Safety and Health Law (Japan) ISO = International Organization for Standardization KECI = Korea Existing Chemicals Inventory LC50 = Lethal Concentration of 50% of a test population LD50 = Lethal Dose of 50% of a test population (Median Lethal Dose) MARPOL = International Convention for the Prevention of Pollution from Ships MSHA = Mine Safety and Health Administration n.o.s. = Not Otherwise Specified NFPA = National Fire Protection Association NO(A)EC = No Observed (Adverse) Effect Concentration NO(A)EL = No Observed (Adverse) Effect Level NOELR = No Observed (Adverse) Effect Loading Rate NTP = National Toxicology Program NZIoC = New Zealand Inventory of Chemicals OECD = Organization for Economic Co-operation and Development OPPTS = Office of Chemical Safety and Pollution Prevention PBT = Persistent, Bio accumulative and Toxic Substances PICCS = Philippines Inventory of Chemicals and Chemical Substances (Q)SAR = (Quantative) Structure Activity Relationship RCRA = Resource Conservation and Recovery Act REACH = Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals RQ = Reportable Quantity SADT = Self-Accelerating Decomposition Temperature SARA = Superfund Amendments and Reauthorization Act SDS = Safety Data Sheet TCSI = Taiwan Chemical Substances Inventory TSCA = Toxic Substances Control Act

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST



(United States) UN = United Nations UNRTDG = United Nations Recommendations on the Transport of Dangerous Goods **vPvB** = Very Persistent and Very Bio accumulative

Prepared by:

PremierRepak, Inc.

http://premierrepak.com/

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

Product: PR 0.65CST Silicone Fluid Revision Date: 2018/10/29 Document: SDS-PRSF 0.65CST