

Section 1 - Chemical Product and Company Identification

Company Information:

 PremierRepak Inc.
 Phone:
 (708) 444-2688

 8351 W. 185th Street
 Fax:
 (708) 429-4280

Tinley Park, IL 60487 www.premierrepak.com

InfoTrac 24-hour Emergency Phone Number: 1 (800) 535-5053

InfoTrac Contract Number: 105384

Product Information:

Substance/Mixture: Mixture

Substance name: Dodecamethylpentasiloxane, C.A.S. Number: 141-63-9

Chemical nature: Silicone

Recommended use: Solvent, Cosmetics, Intermediate

Section 2 - Classifications

GHS Classification: Flammable liquids: Category 4

Signal Word: WARNING

Hazard Statements:

H227: Combustible liquid.

Precautionary Statements:

Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P280: Wear protective gloves/ eye protection/ face protection.

Response:

P370: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235: Store in a well-ventilated place. Keep cool.

Disposal:

P501: Dispose of contents/container to an approved waste disposal plant.

Other hazards: No data available.

Section 3 – Composition and Information on Ingredients

Hazardous Ingredients:

Common NameC.A.S. No.Wt. %Dodecamethylpentasiloxane141-63-9>=90.0-<=100.0 %</td>



Section 4 - First Aid Measures

First Aid Measures:

General Advice: If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Skin contact: Wash off with plenty of water.

Inhalation: No emergency medical treatment necessary. **Ingestion:** No emergency medical treatment necessary.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2

minutes and continue flushing for several additional minutes. If effects occur, consult a physician,

preferably an ophthalmologist.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed:

Note to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and clinical condition of the patient.

Section 5 – Firefighting Measures

Suitable extinguishing media: Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO2)

Unsuitable extinguishing media: High volume water jet. Do not use direct water stream.

Specific hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides, Silicon oxides.

Unusual Fire and Explosion Hazards: Flash back possible over considerable distance. Exposure to combustion products may be a hazard to health. Fire burns more vigorously than would be expected. Vapors may form explosive mixtures with air.

Advice for firefighters

Firefighting Procedures: Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Do not use a solid water stream as it may scatter and spread fire. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for fire fighters: Wear self-contained breathing apparatus for firefighting if necessary Use personal protective equipment.

Section 6 – Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Remove all sources of ignition. Follow safe handling advice and personal protective equipment recommendations.



Environmental precautions:

Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained. Prevent spreading over a wide area (e.g. by containment or oil barriers).

Methods and materials for containment and cleaning up:

Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

Section 7- Handling and Storage

Precautions for safe handling:

Handle in accordance with good industrial hygiene and safety practice. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Use with local exhaust ventilation.

See Engineering measures under SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

Conditions for safe storage:

Keep in properly labeled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition. Do not store with the following product types: Strong oxidizing agents, Explosives, Gases. Unsuitable materials for containers: None known

Section 8 – Exposure Controls and Personal Protection

Control parameters:

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Exposure controls:

Engineering Controls:

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limits or guidelines, general ventilation should be sufficient for most operations. Processing may form hazardous compounds (see section 10). Minimize workplace exposure concentrations.

Individual protective measures:

Eye/face protection: Use safety glasses (with side shields).



Skin protection:

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"), Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed: however, if discomfort is experienced, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

Section 9 – Physical/Chemical Characteristics

Appearance:

Physical state: Liquid Color: Colorless Odor: None

Odor Threshold: No data available.

Freezing Point: No data available.

Melting Point Range: No data available.

Boiling Point (760mmHg): 230 degrees Celsius (446 degrees F)

Vapor Pressure: No data available.

Relative Vapor Density (air=1): No data available.

Solubility in Water: No data available.

pH: No data available.

Flash Point: 87 degrees Celsius (189 degrees F): Method: Tag closed cup

Auto-ignition Temperature: No data available. **Flammability (solid, gas):** Not applicable.

Evaporation rate (Butyl Acetate=1): No data available.

Upper explosion limit: No data available. **Lower explosion limit:** No data available.

Partition coefficient: n-octanol/water: No data available. Decomposition temperature: No data available.

Viscosity, kinematic: 2cSt at 25 degrees Celsius (77 degrees F)

Explosive properties: Not explosive.

Oxidizing properties: The substance or mixture is not classified as oxidizing.

Relative Density (Water=1): 0.872 Molecular weight: No data available.

Particle Size: Not applicable.

Product: PR 2CST Silicone Fluid Revision Date: 2019/06/19
Occument: SDS-PRSF 7CST Revision #: 6.2



NOTE: The physical data presented above are typical values and should not be construed as a specification.

Section 10 – Stability and Reactivity

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions:

Combustible liquid. Vapors may form explosive mixture with air. Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required.

Conditions to avoid: Heat, flames and sparks.

Incompatible materials: Oxidizing agents

Hazardous decomposition products: Thermal decomposition: Formaldehyde

Section 11 – Toxicological Information

Toxicological information appears in this section when such data is available.

Acute toxicity:

Acute Oral toxicity:

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

Based on information for component(s): LD50 (Rat, male/female): < 5000 mg/kg. No deaths occurred at this concentration.

Acute Dermal toxicity:

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Based on information for component(s): LD50 (Rat): < 2,000 mg/kg. No deaths occurred at this concentration.

Acute Inhalation toxicity:

No adverse effects are anticipated from inhalation. As product: The LC50 has not been determined.

Skin corrosion/irritation:

Brief contact is essentially non-irritating to skin.

Serious eye damage/eye irritation:

May cause slight temporary eye irritation. Corneal injury is unlikely. May cause mild eye comfort.

Product: PR 2CST Silicone Fluid Revision Date: 2019/06/19
Document: SDS-PRSF 2CST Revision #: 6.2



Sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization: No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure): Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure): Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity: No relevant data found.

Teratogenicity: For this family of material(s): Did not cause birth defects in laboratory animals.

Mutagenicity: For this family of material(s): In vitro genetic toxicity studies were predominately negative.

Reproductive toxicity: For similar material(s): In animal studies, did not interfere with fertility. In animal studies, did not interfere with reproduction.

Aspiration Hazard: Based on available information, aspiration hazard could not be determined.

Components Influencing Toxicology:

Dodecamethylpentasiloxane:

Acute inhalation toxicity: The LC50 has not been determined.

Section 12 – Ecological Information

Ecotoxicological information appears in this section when such data is available.

Toxicity:

<u>Dodecamethylpentasiloxane:</u>

Acute toxicity to fish: Not expected to be acutely toxic to aquatic organisms. No toxicity at the limit of solubility. LC50, *Oncorhynchus mykiss* (rainbow trout), 96 Hour, > 0.000075 mg/l, OECD Test Guideline 203.

Acute toxicity to algae/aquatic plants: No toxicity at the limit of solubility. EC50, *Pseudokirchnerella subcapita* (green algae), 72 Hour, < 0.035 microgram/l.

Chronic toxicity to aquatic invertebrates: No toxicity at the limit of solubility. NOEC, *Daphnia magna* (Water flea), 21 d, 0.000047 mg/l.

Persistence and degradability:

Dodecamethylpentasiloxane:

Biodegradability: No appreciable biodegradation is expected.

Product: PR 2CST Silicone Fluid Revision Date: 2019/06/19
Occument: SDS-PRSF 2CST Revision #: 6.7



10-day window: Not applicable.

Biodegradation: 0% Exposure time: 28 d

Method: OECD Test guidelines 310

Bioaccumulative potential:

Dodecamethylpentasiloxane:

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow

between 3 and 5).

Partition Coefficient: n-octanol/water (log Pow): 9.26

Bioconcentration factor (BCF): 170

Mobility in soil:

Dodecamethylpentasiloxane:

Expected to be relatively immobile in soil (Koc): >5000

Partition Coefficient (Koc): >5000

Section 13 – Disposal Considerations

Disposal methods:

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES ORMANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THEINFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information.

FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15.

Treatment and disposal methods of used packaging:

Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

Section 14 – Transport Information

Domestic regulation:

DOT:

UN/ID/NA number: NA 1993

Proper shipping name: COMBUSTIBLE LIQUID, N.O.S. (Dodecamethylpentasiloxane)

Class: CBL Packing group: III Labels: None



ERG Code: 128 Marine pollutant: no

Remarks: Above applies only to containers over 119 gallons or 450 liters. Not regulated if shipped in

packages less than or equal to 119 gallons (450 liters).

International Regulation:

UNRTDG: Not regulated as a dangerous good

Classification for AIR transport: IATA-DGR: Not regulated for transport.

Classification for SEA transport: IMDG-Code: Not regulated for transport.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Consult IMO

regulations before transporting ocean bulk

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Section 15 - Hazard Classification

EPCRA (Emergency Planning and Community Right-to-Know):

CERCLA Reportable Quantity Section 103:

Component Name CAS Number Component RQ (lbs) Calculated product RQ(lbs)
NONE

SARA 304 Extremely Hazardous Substances Reportable Quantity:

<u>Component Name</u> <u>CAS Number</u> <u>Component RQ (lbs)</u> <u>Calculated product RQ(lbs)</u>
NONE

SARA 311/312 Hazards: Flammable (gases, aerosols, liquids, or solids)

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations:

California:

Warning: This product does NOT contain the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

Component Name CAS Number NONE



State Right-To-Know:

CAS Number	Wt %	Component Name	State State
141-63-9	90 – 100	Dodecamethylpentasiloxane	Pennsylvania

The ingredients of this product are reported in the following inventories:

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances

Section 16 - Other Information

Further information:

HMIS: Health: 1 Flammability: 0 Reactivity: 0 Personal Protection: E NFPA: Health: 1 Flammability: 0 Reactivity: 0 Special: None

HMIS Classification and NFPA Rating: 0 = Insignificant

1 = Slight 2 = Moderate 3 = High 4 = Extreme

Full text of other abbreviations:

AICS = Australian Inventory of Chemical Substances ASTM = American Society for the Testing of Materials bw = body weight **CERCLA** = Comprehensive Environmental Response, Compensation, and Liability Act **CMR** = Carcinogen, Mutagen or Reproductive Toxicant DIN = Standard of the German Institute for Standardization DOT = Department of Transportation DSL = Domestic Substances List (Canada) ECx = Concentration associated with x% response EHS = Extremely Hazardous Substance ELx = Loading rate associated with x% response EmS = Emergency Schedule ENCS = Existing and New Chemical Substances (Japan) ErCx = Concentration associated with x% growth rate response ERG = Emergency Response Guide GHS = Global Harmonization System GLP = Good Laboratory Practice HMIS = Hazardous Material Identification System IARC = The International Agency for Research on Cancer IATA = International Air Transportation Association IBC = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk IC50 = Half maximal inhibitory concentration ICAO = International Civil Aviation Organization IECSC = Inventory of Existing Chemical Substances in China IMDG = International Maritime Dangerous Goods IMO = International Maritime Organization ISHL = Industrial Safety and Health Law (Japan) ISO = International Organization for Standardization KECI = Korea Existing Chemicals Inventory LC50 = Lethal Concentration of 50% of a test population LD50 = Lethal Dose of 50% of a test population (Median Lethal Dose) MARPOL = International Convention for the Prevention of Pollution from Ships MSHA = Mine Safety and Health Administration n.o.s. = Not Otherwise Specified NFPA = National Fire Protection Association NO(A)EC = No Observed (Adverse) Effect Concentration NO(A)EL = No Observed (Adverse) Effect Level NOELR = No Observed (Adverse) Effect Loading Rate NTP = National Toxicology Program NZIoC = New Zealand Inventory of Chemicals **OECD** = Organization for Economic Co-operation and Development **OPPTS** = Office of Chemical Safety and Pollution Prevention PBT = Persistent, Bio accumulative and Toxic Substances PICCS = Philippines Inventory of Chemicals and Chemical Substances (Q)SAR = (Quantative) Structure Activity Relationship RCRA = Resource

Product: PR 2CST Silicone Fluid Revision Date: 2019/06/19
Oncument: SDS-PRSF 7CST Revision #: 6.2



Conservation and Recovery Act **REACH** = Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals **RQ** = Reportable Quantity **SADT** = Self-Accelerating Decomposition Temperature **SARA** = Superfund Amendments and Reauthorization Act **SDS** = Safety Data Sheet **TCSI** = Taiwan Chemical Substances Inventory **TSCA** = Toxic Substances Control Act

(United States) **UN** = United Nations **UNRTDG** = United Nations Recommendations on the Transport of Dangerous Goods **vPvB** = Very Persistent and Very Bio accumulative

Prepared by:

PremierRepak, Inc.

http://premierrepak.com/

PREMIERREPAK urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer specific SDSs, we are not and cannot be responsible for SDSs obtained from any source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.