PREMIER**REPAK**, INC

Product Guide



Innovative Ideas...Moving You Forward

PREMIER REPAK

Innovative Ideas...Moving You Forward

The industrial distribution market needs top quality silicone sealants, lubricants and related products at a reasonable price in a timely manner.

PremierRepak, Inc. was created to meet those needs. We are one of the most highly respected names in the industry. And, as a result of low overhead expenses and in-house capabilities, we can offer our customers a large and diverse inventory, low minimum orders and shipping in a timely manner.

Our continuous investment in the best equipment, facilities and people has given us the ability to present our customers with a wider range of services - from manufacturing and repackaging to private label and turnkey services.

Our commitment to premium products and a higher level of customer and technical services, allows us to create unique customer driven solutions to help move them forward in today's market.

Look to PREMIERREPAK for your most challenging needs.

Innovative ideas...Moving You Forward

8351 185th Street • Tinley Park, IL 60487 • ph: 855.737.2500 • fax: 708.429.4280 customerservice@premierrepak.com • www.premierrepak.com

PremierRepak is an ISO9001:2015 facility

To Order Call: 855.737.2500

Table of Contents

Products

Silicone Sealants	<u>4-6</u>
Silicone Compounds	7-8
Silicone Greases	9-10
Silicone Fluids	11

Services

Private Label & Repackaging	<u> 12</u>
Contract Packaging	12
Turnkey Solutions	13









Innovative Ideas... Moving You Forward

SILICONE SEALANTS

- One component RTV silicone adhesive/sealants designed for a wide variety of industrial applications and general purpose bonding.
- Excellent adhesion to glass, tile, steel, aluminum, wood, plastic and many other substrates.
- Fully cured sealants can be used at temperatures ranging from -55° to 500°F (-48° to 260°C).

PremierRepak 2200 Industrial Grade Silicone Sealant

Used for a wide variety of industrial applications & general bonding requirements.

Sizes: 10.1oz (300ml) caulk cartridge, 5 gal (17.4kg) pail and 52 gal (205kg) drum

Colors: Aluminum, Black, Clear & White

Cure Type: Acetoxy

Specifications & Listings: NSF/ANSI Std 51, UL QMFZ2, QMFZ8 & FDA Reg No. 21, CFR 177.2600

Temp Range: -76°F to 350°F, (-60°C to 177°C)

Intermittent Temp: 400°F, (204°C)

Size	Aluminum	Black	Clear	White
10.1oz (300ml) cartridge	2200AC	2200BC	2200CC	2200WC
5 gal (17.4kg) pail	2200AP	2200BP	2200CP	2200WP
52 gal (205kg) drum	2200AD	2200BD	2200CD	2200WD

PremierRepak 2202 Multi-Purpose Silicone Sealant

Used for general purpose bonding & sealing, making formed-in-place-gaskets.

Sizes: 3.0oz (90ml) tube, 10.1oz (300ml) caulk cartridge, 5 gal (17.4kg) pail and 52 gal (205kg) drum

Colors: Aluminum, Black, Clear & White

Cure Type: Acetoxy

Specifications & Listings: NSF/ANSI Std 51, UL QMFZ2, QMFZ8 & FDA Reg No. 21, CFR 177.2600,

MIL Spec A-46106B

Temp Range: -76°F to 350°F, (-60°C to 177°C)

Intermittent Temp: 400°F, (204°C)

Size	Aluminum	Black	Clear	White
3.0oz (90ml) tube			2202CT90	2202WT90
10.1oz (300ml) cartridge	2202AC	2202BC	2202CC	2202WC
5 gal (17.4kg) pail	2202AP	2202BP	2202CP	2202WP
52 gal (205kg) drum	2202AD	2202BD	2202CD	2202WD

PremierRepak 2203 Glass & Metal Silicone Sealant

Used for improved, unprimed adhesion to glass, metal and other surfaces.

Sizes: 10.1oz (300ml) caulk cartridge, 5 gal (17.7kg) pail and 52 gal (205kg) drum

Color: Clear

Cure Type: Acetoxy

Temp Range: -76°F to 350°F, (-60°C to 177°C)

Intermittent Temp: 400°F, (204°C)

Size	Clear
10.1oz (300ml) cartridge	2203CC
5 gal (17.4kg) pail	2203CP
52 gal (205kg) drum	2203CD



Innovative Ideas... Moving You Forward

PremierRepak 2206 High Temperature Silicone Sealant

Formulated for higher temperature resistance than standard silicone sealants.

Sizes: 10.1oz (300ml) caulk cartridge, 5 gal (17.7kg) pail and 52 gal (205kg) drum

Color: Red

Cure Type: Acetoxy

Specifications & Listings: NSF/ANSI Std 51, UL QMFZ2, QMFZ8 & FDA Reg No. 21, CFR 177.2600

Temp Range: -76°F to 500°F, (-60°C to 260°C)

Intermittent Temp: 600°F, (315°C)

Size	Red
10.1oz (300ml) cartridge	2206C
5 gal (17.4kg) pail	2206P
52 gal (205kg) drum	2206D

PremierRepak 2207 Neutral Cure Silicone Sealant

A primer less adhesion to a wide variety of substrates, with a low odor, oxime cure.

Sizes: 10.1oz (300ml) caulk cartridge, 5 gal (17.6kg) pail and 52 gal (205kg) drum

Color: Black, Clear, White

Cure Type: Oxime

Temp Range: -80°F to 350°F, (-62°C to 177°C)

Intermittent Temp: 400°F, (204°C)

Size	Black	Clear	White
10.1oz (300ml) cartridge	2207BC	2207CC	2207WC
5 gal (17.6kg) pail	2207BP	2207CP	2207WP
52 gal (205kg) drum	2207BD	2207CD	2207WD

PremierRepak 2210 Door & Window Silicone Back Bedding Sealant

Used as a bedding seal in the construction of residential and commercial doors & windows and for general purpose sealing.

Sizes: 10.1oz (300ml) caulk cartridge

Color: Clear

Specifications & Listings: ATSM C920 Standard Specification for Elastomeric Joint Sealants; Type S,

Grade NS,

Class 25, Use A, G, O.

Temp Range: -55°F to 300°F, (-48°C to 149°C)

Size	Clear
10.1oz (300ml) cartridge	2210TC



Innovative Ideas... Moving You Forward

SILICONE COMPOUNDS

- Grease-like materials composed of silicone fluids and silica fillers.
- Used for their sealing, dielectric, non-metal to metal lubricating & release properties.

PremierRepak 5501 High Consistency Silicone Valve & O-ring Lubricant

A viscous, thick and tacky O-ring and valve lubricant.

Sizes: 5.2oz (150g) tube, 14.1oz (400g) grease cartridge, 1 gal (3.6kg) pail, 5 gal

(18.1kg) pail, NLGI #: 3

Specifications & Listings: FDA, NSF61

Temp Range: -40°F to 400°F, (-40°C to 204°C)

Size	Part #
5.2oz (150g) tube	PR5501-T150
14.1oz (400g) grease cartridge	PR5501-GC400 *
1 gal (3.6kg) pail	PR5501-P3.6 *
5 gal (18.1kg) pail	PR5501-P18.1 *

^{*}Cartridge/Pail sizes for this item are not readily available, but are available through special order. Please call or email customer service for volumes.

PremierRepak 5504 Medium Consistency Silicone Valve & O-ring Lubricant

Dielectric moisture barrier on electrical equipment and general purpose O-ring & valve lubricant.

Sizes: 5.2oz (150g) tube, 14.1oz (400g) grease cartridge, 1 gal (3.6kg) pail, 5 gal

(18.1kg) pail, **NLGI #:** 2 to 3

Specifications & Listings: FDA

Temp Range: -40°F to 400°F, (-40°C to 204°C)

Size	Part #
5.2oz (150g) tube	PR5504-T150
14.1oz (400g) grease cartridge	PR5504-GC400 *
1 gal (3.6kg) pail	PR5504-P3.6 *
5 gal (18.1kg) pail	PR5504-P18.1 *

^{*}Cartridge/Pail sizes for this item are not readily available, but are available through special order. Please call or email customer service for volumes.

PremierRepak 5507 Low Consistency Silicone Valve & O-ring Lubricant

A release and parting agent for plastic and metal surfaces.

Sizes: 5.2oz (150g) tube, 14.1oz (400g) grease cartridge, 1 gal (3.6kg) pail, 5 gal (18.1kg) pail

NLGI#: 1

Specifications & Listings: FDA

Temp Range: -40°F to 400°F, (-40°C to 204°C)

Size	Part #
5.2oz (150g) tube	PR5507-T150
14.1oz (400g) grease cartridge	PR5507-GC400 *
1 gal (3.6kg) pail	PR5507-P3.6 *
5 gal (18.1kg) pail	PR5507-P18.1 *

^{*}Cartridge/Pail sizes for this item are not readily available, but are available through special order. Please call or email customer service for volumes.



Innovative Ideas...Moving You Forward

SILICONE GREASES

- Solid to semisolid materials consisting of a lubricating fluid, thickening agent & additives.
- Designed for use under extreme conditions, harsh chemical environments, low & high temperatures and all speed.
- Reduces friction & wear, maintenance & replacement costs and extends lubrication time.

PremierRepak 6701 Polyurea Grease

Ideally suited for use in applications where heavy metal additives are prohibited such as electric motor bearings.

Sizes: 14.1oz (400g) grease cartridge, 4.2 gal (16kg) pail, 14.5 gal (55kg) keg

Thickener: Polyurea

NLGI#: 2

Temp Range: -20°F to 450°F, (-29°C to 232°C)

Size	Part #
14.1oz (400g) grease cartridge	PR6701-GC400
4.2 gal (16kg) pail	PR6701-P16
14.5 gal (55kg) keg	PR6701-K55

SILICONE FLUID

- A polydimethylsiloxane fluid.
- Used as a release agent or coating, alone or as part of a compound formula.
- Provides a non-carbonizing mold release for high temperature and long life rubber, plastic and metal die castings.

PremierRepak 200 General Purpose Silicone Fluid

Sizes: 16.9oz (500ml) bottle, 5 gal (18.1kg) pail, 52 gal (205kg) drum

CST: Centistoke

FG: Food Grade rated

Centistoke	16.9oz (500ml) Bottle	5 gal Pail	Drum
.65 CST	PRSF20065-B500	PRSF20065-P13	PRSF20065-D190
1 CST	PRSF200-1-B500	PRSF200-1-P16	PRSF200-1-D190
2 CST	PRSF200-2-B500	PRSF200-2-P16	PRSF200-2-D180
5 CST	PRSF200-5-B500	PRSF200-5-P16	PRSF200-5-D190
10 CST	PRSF200-10-B500	PRSF200-10-P16	PRSF200-10-D190
20 CST	PRSF200-20-B500	PRSF200-20-P16	PRSF200-20-D200
50 CST	PRSF200-50-B500	PRSF200-50-P18	PRSF200-50-D200
100 CST	PRSF200-100-B500	PRSF200-100-P18	PRSF200-100-D200
200 CST	PRSF200-200-B500	PRSF200-200-P18	PRSF200-200-D200
350 CST	PRSF200-350-B500	PRSF200-350-P18	PRSF200-350-D200
350 CST FG	PRSF200-350FG-B500	PRSF200-350FG-P18	PRSF200-350FG-D200
500 CST	PRSF200-500-B500	PRSF200-500-P18	PRSF200-500-D200
1,000 CST	PRSF200-1000-B500	PRSF200-1000-P18	PRSF200-1000-D200
1,000 CST FG	PRSF200-1000FG-B500	PRSF200-1000FG-P18	PRSF200-1000FG-D200
5,000 CST	PRSF200-500-BS500	PRSF200-500-P18	PRSF200-500-D200
10,000 CST	PRSF200-10000-B500	PRSF200-10000-P16	PRSF200-10000-D200
12,500 CST	PRSF200-12500-B500	PRSF200-12500-P16	PRSF200-12500-D200
30,000 CST	PRSF200-30000-B500	PRSF200-30000-P16	PRSF200-30000-D200

PREMIER REPAK

Innovative Ideas...Moving You Forward

60,000 CST	PRSF200-60000-B500	PRSF200-60000-P16	PRSF200-60000-D200
100,000 CST	PRSF200-100000-B500	PRSF200-100000-P16	PRSF200-100000-D195

PRIVATE LABEL & REPACKAGING

We can provide a full range of private label packaging services whether you choose to sell PremierRepak's silicone sealant under your company's brand and logo or if you need other material repackaged and labeled per your specifications, PremierRepak has the knowledge and insight to guide you through the process.

We offer 3 different labeling options designed to fit any budget:

- 1. Printed artwork directly onto the container.
- 2. Design and create labels that adhere to the container.
- 3. A shrink wrapped sleeve that creates a clear, sharp finished product on the container.

PremierRepak utilizes a broad range of packing styles and products:

- Monopacks Tubes
- MixpacPails
- BottlesDrums
- CartridgesTwin Syringes

Look to PremierRepak to for your next private label or repackaging need.

CONTRACT PACKAGING

PremierRepak has numerous packaging capabilities ready to meet your specific need. We are equipped with some of the most modern, industrial mixing equipment around. We have the capability to mix small orders of 48 cartridges to large orders of 20 pallets or more.

Through our Color Plus Mixing Program, we are able to offer custom color matching of virtually any color whether an industry standard or a specific customer color.

Our Value-Added services include secondary packaging, hand assembly, displays and drop ships.

We have the ability to package:

- · Adhesives, lubricants, silicones, sealants, epoxies, caulk and fillers
- Viscose liquids, various temperatures
- Petroleum based items
- Chemicals, detergents, cleaners and greases
- Polishes and pastes
- Powders and granules

Give us a call and to see how PremierRepak can help meet your specific packing needs.

TURNKEY PACKAGING & SOLUTIONS

Let PremierRepak take responsibility of your project from start to finish. We will work with you to determine the proper scope of service needed; from beginning with raw material, choosing a specific container, customizing the label and ending with the finished product, PremierRepak will perform the exact steps to get you project done in a timely matter and with the highest quality.

We offer complete one stop shopping:

- Custom formulation compounding, blending and filling based on your requirements
- Chemical toll blending
- Packaging, private labeling (in-line)
- · In house labeling and design service
- Shrink and sleeve wrapping
- · Machine and hand assembly
- · On site laboratory and specification testing
- Warehousing and distribution

Let PremierRepak's experience and capabilities take the worry out of your next turnkey project.

PREMIERREPAK, INC

Innovative Ideas...Moving You Forward

8351 185th Street • Tinley Park, IL 60487 • ph: 855.737.2500 • fax: 708.429.4280

<u>customerservice@premierrepak.com</u> • www.premierrepak.com